



Roxtec B Ex 관통 장비

유연한 조합을 지원하는 프레임을 갖춘

Roxtec B Ex는 Ex e 및 Ex tb 구역에 설치 가능한 다중 케이블 및 파이프 트랜지트입니다. 개방형 금속 프레임은 서로 다른 크기와 조합을 형성하기 위해 함께 볼트로 고정된 다음 기존 케이블이나 파이프 주위를 개선하거나 새로운 구조물에 사용하기 위해 구조물에 설치됩니다. Roxtec Ex 씰링 모듈은 다른 크기의 케이블과 파이프에 적용 가능하며 씰에 여유 공간을 만들 수도 있습니다.

- 유지/보수 용이



제품 특징점



내화



IP/UL NEMA



Ex 등급



EMI 보

설치 구조



캐비닛 및 인클로저



금속



콘크리트

장착 유형



볼트체결



주물

등급 및 인증

화재

- EN 13501에 따른 E/EI 등급
- UL 1479에 따른 F/T 등급

강도

- IP 54

지원

- 등전위화
- Ex 등급

프레임 치수

mm/kg

아래의 프레임 변화는 제한된 선택입니다. 프레임 및 구성의 전체 범위를 보려면 [roxtec.com](https://www.roxtec.com)을 방문하십시오.

구성	프레임 입구	모듈설치공간	외부 치수 WxHxD	홀 치수 w x h	무게	Art. 번호
B 6x1 B Ex GALV	1	120 x 180	200.5 x 298 x 60	146(+1/-1) x 243(+1/-1)	3.7	EXBBB0600000115
B 6x1 C Ex GALV	1	120 x 180	200.5 x 298 x 60	146(+1/-1) x 243(+1/-1)	3.6	EXBBC0600000115
B 6x2 B Ex GALV	2	120 x 180	329 x 298 x 60	274(+1/-1) x 243(+1/-1)	6.1	EXBBB0600000215
B 6x2 C Ex GALV	2	120 x 180	329 x 298 x 60	274(+1/-1) x 243(+1/-1)	5.9	EXBBC0600000215
B 6x3 B Ex GALV	3	120 x 180	457.5 x 298 x 60	403(+1/-1) x 243(+1/-1)	8.7	EXBBB0600000315
B 6x3 C Ex GALV	3	120 x 180	457.5 x 298 x 60	403(+1/-1) x 243(+1/-1)	8.6	EXBBC0600000315



씰링 컴포넌트 데이터

씰링 컴포넌트


액세서리



윤활제



Wedge 및 We



RM Ex 모듈(M ultidiamet




RM Ex 솔리드




스테이플레이트 Ex



홀더 도구



RM PE Ex 모듈(Multidiameter 포함)



RM PE Ex 솔



Ex 씰링 키트

자세한 내용은 [roxtec.com](https://www.roxtec.com)을 방문하십시오.

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use. Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended. Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses. The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>. We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright. This document was generated on: 2024-04-19