




配有 SL R 的 Roxtec R 防爆穿隔系统

用于密封受限区域内的多根电缆和管道时进行焊接安装的防爆级圆形穿隔系统。

配有 SL R 的 Roxtec R Ex 是一种用于 Ex e 和 Ex tb 区域的电缆和管道穿隔系统。它是专为圆孔开发的并带有可焊接到结构上的套筒。压紧件已集成在密封件上并通过膨胀密封。Roxtec 防爆密封模块可灵活适配各种规格的电缆和管道并可用于在密封系统内提供备用容量。穿隔框架的背面有一个网子可用于水平安装（不包括在 R 70 和 R 75 中）。



- 节省空间
- 易于维护和检查

产品特性



耐火



水密



气密



防爆等级

安装结构



金属



分层结构

安装类型



焊接

等级和证书

火灾

- A 级符合 IMO 2010 FTP 规范
- H 级符合 IMO 2010 FTP 规范 + HC 火灾荷载曲线

密封性

- 气体: 2.5 bar 洪水
- 水: 4 bar 洪水

支持

- 防爆等级

框架尺寸

mm/kg

下方的不同框架只是部分选择。要了解全部的框架和配置请访问 [roxtec.com](https://www.roxtec.com)。

标题	密封空间	开孔尺寸 Ø	重量	产品编号
R 200 W Ex AISI316/AISI316	120 x 120	216 - 216	5.3	EXWR00002002121
R 200 W Ex AISI316/PRIMED	120 x 120	216 - 216	5.3	EXWR00002002112
R 75 W Ex AISI316/AISI316	40 x 40	91 - 91	1.4	EXWR00000752121
R 75 W Ex AISI316/PRIMED	40 x 40	91 - 91	1.4	EXWR00000752112
R 100 W Ex AISI316/AISI316	60 x 60	116 - 116	2.1	EXWR00001002121
R 100 W Ex AISI316/PRIMED	60 x 60	116 - 116	1.9	EXWR00001002112
R 125 W Ex AISI316/AISI316	80 x 80	142 - 142	2.7	EXWR00001252121
R 125 W Ex AISI316/PRIMED	80 x 80	142 - 142	2.8	EXWR00001252112
R 150 W Ex AISI316/AISI316	90 x 90	166 - 166	3.5	EXWR00001502121
R 150 W Ex AISI316/PRIMED	90 x 90	166 - 166	3.5	EXWR00001502112



The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2024-02-24