



Roxtec RS Ex seal with SL RS

Ex rated seal for welding, for a single cable or pipe.

The Roxtec RS Ex with SL RS is a seal rated for Ex e and Ex tb areas. It has a metal sleeve and is designed for single cables or pipes. The entry seal has two halves with removable layers making it adaptable to cables and pipes of different sizes. The sleeve is welded to the structure.



- Rodent resistant
- Quick and easy to install

Product characteristics



Fire rated



Watertight



Gas-tight



Ex rated

Structure of installation



Metal

Mounting type



Welding

Ratings & certificates

Fire

- A-CLASS according to IMO 2010 FTP Code
- H-CLASS according to IMO 2010 FTP Code + HC fire load curve
- Jet fire according to ISO 22899-1 and OTI 95634

Tightness

- Gas: 2.67 bar (catastrophic)
- Water: 4 bar (catastrophic)

Supports

- Ex rated

Sealing components

Sealing components




RS W Ex kit

For detailed information, please visit [roxtec.com](https://www.roxtec.com).

Pre-configured transit kits

in/lbs



Product	Configuration	Aperture dimensions Ø	Weight	Art. no
RS 100 W Ex AISI316/AISI316			5	EXRSW1000002121
RS 25 W Ex AISI316/PRIMED	1x (0.142-0.472)	0.984 - 1.024	0.37	EXRSW0250002112
RS 125 W Ex AISI316 WOC/PRIMED	1x (2.598-3.858)	4.921 - 5	6.4	EXRSW0125102112
RS 150 W Ex AISI316 WOC/AISI316	1x (3.661-4.685)	5.906 - 5.984	7.1	EXRSW0150102121
RS 100 W Ex AISI316/PRIMED			5	EXRSW1000002112
RS 75 W Ex AISI316/AISI316	1x (0.945-2.126)	2.953 - 3.031	3.3	EXRSW0750102121
RS 50 W Ex AISI316/AISI316	1x (0.315-1.181)	1.969 - 2.047	2.1	EXRSW0500002121
RS 43 W Ex AISI316/AISI316	1x (0.157-0.906)	1.693 - 1.772	1.2	EXRSW0430102121
RS 75 W Ex AISI316/PRIMED	1x (0.945-2.126)	2.953 - 3.031	3.3	EXRSW0750002112
RS 125 W Ex AISI316 WOC/AISI316	1x (2.598-3.858)	4.921 - 5	7.1	EXRSW0125102121
RS 43 W Ex AISI316/PRIMED	1x (0.157-0.906)	1.693 - 1.772	1.4	EXRSW0430002112
RS 125 W Ex AISI316/PRIMED			7	EXRSW1250002112
RS 125 W Ex AISI316/AISI316			7.2	EXRSW1250002121
RS 100 W Ex AISI316 WOC/PRIMED	1x (1.890-2.756)	3.937 - 4.016	4.3	EXRSW0100102112
RS 25 W Ex AISI316/AISI316	1x (0.142-0.472)	0.984 - 1.024	0.53	EXRSW0250002121
RS 100 W Ex AISI316 WOC/AISI316	1x (1.890-2.756)	3.937 - 4.016	5.1	EXRSW0100102121
RS 150 W Ex AISI316 WOC/PRIMED	1x (3.661-4.685)	5.906 - 5.984	7.1	EXRSW0150102112
RS 50 W Ex AISI316/PRIMED	1x (0.315-1.181)	1.969 - 2.047	2	EXRSW0500002112

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2024-04-27