



Roxtec HD BG™ 관통 장비

본딩(Bonding) 및 접지용 고밀

Roxtec HD 32 BG™는 열악하고 위험한 환경에서 3가지 종류의 사이즈로 이용할 수 있는 외장 및 금속 피복 케이블의 접지, 씰링에 사용되는 케이블 인입구 장비입니다. 케이블 관통 장비는 오프닝마다 최대 32개의 케이블을 허용합니다. 이 제품에는 316L 스테인리스 스틸 프레임과 다양한 케이블 규격에 맞는 Roxtec BG™ 씰링 모듈이 있습니다.



- 설치류 차단
- 부식 방지
- 경량
- 공간 효율성
- 케이블 말단 처리 허용

제품 특징점



IP/UL NEMA



전기관련

설치 구조



캐비닛 및 인클로저

등급 및 인증

강도

- IP 66/67, UL/NEMA 4,4X,12,13

지원

- Bonding과 Grounding

프레임 치수


mm/kg

아래의 프레임 변화는 제한된 선택입니다. 프레임 및 구성의 전체 범위를 보려면 [roxtec.com](https://www.roxtec.com)을 방문하십시오.


구성	프레임 입구	모듈설치공간	외부 치수 WxHxD	홀 치수 w x h	무게	Art. 번호
HD 16 FRAME ASSEMBLY AISI 316	1	40 x 160	83.8 x 236 x 60	64(+1/-0.5) x 216(+1/-0.5)	1.6	193084
HD 32 FRAME ASSEMBLY AISI316	2	40 x 160	130 x 236 x 60	110(+1/-0.5) x 216(+1/-0.5)	2.3	109238

씰링 컴포넌트 데이터

씰링 컴포넌트



CM BG™ 모듈(Multidiam)



CM BG™ 솔리드



윤활제

자세한 내용은 [roxtec.com](https://www.roxtec.com)을 방문하십시오.



키트 구성의 관통장비

mm/kg



HD 16/4 BG



HD 16/10 BG



HD 16/16 BG



HD 32/8 BG B KIT



HD 32/32 BG B KIT



HD 32/20 BG B KIT



HDLC/24+2 BG

구성	구성	외부 치수 WxHxD	홀 치수 w x h	무게	Art. 번호
HD 16/4 BG	4x (9.5-32.5)	83.8 x 236 x 60	64(+1/-0.5) x 216(+1/-0.5)	2	193105
HD 16/10 BG	2x (9.5-32.5), 8x (3.5-16.5)	83.8 x 236 x 60	64(+1/-0.5) x 216(+1/-0.5)	2	198299
HD 16/16 BG	16x (3.5-16.5)	83.8 x 236 x 60	64(+1/-0.5) x 216(+1/-0.5)	2	193104
HD 32/8 BG B KIT	8x (9.5-32.5)	130 x 236 x 60	110(+1/-0.5) x 216(+1/-0.5)	3.3	120373
HD 32/32 BG B KIT	32x (3.5-16.5)	130 x 236 x 60	110(+1/-0.5) x 216(+1/-0.5)	3.5	120374
HD 32/20 BG B KIT	4x (9.5-32.5), 16x (3.5-16.5)	130 x 236 x 60	110(+1/-0.5) x 216(+1/-0.5)	3.4	120376
HDLC/24+2 BG	2x (24.0-54.0), 24x (3.5-16.5)	378 x 120 x 94	366(+1/-1) x 108(+1/-1)	5.6	173280

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2024-04-18