



# Roxtec HD BG™-gjennomføringer

Gjennomføringsutstyr for høy kabeltetthet beregnet på jording.

Roxtec HD BG™ er kabelinngangsutstyr for tetning og jording av armerte eller metallklede kabler i røffe og risikoutsatte miljøer, og de leveres i tre ulike størrelser. Kabelgjennomføringen tillater opptil 32 kabler per åpning. Den har en 316L rustfri stålramme og Roxtec BG™-moduler som kan tilpasses en rekke forskjellige kabelstørrelser.



- Skadedyrbestandig
- Korrosjonsbestandig
- Lettvekt
- Arealeffektiv
- Godkjent for kabelavslutning

## Produktegenskaper



IP/UL NEMA



Elektrisk sikkerhet

## Struktur for installasjon



Kabinetter og kapslinger

## Graderinger og sertifikater

### Tetthet

- IP 66/67, UL/NEMA 4,4X,12,13

### Støtter

- Jording og potensialutjevning (bonding and grounding)

## Rammedimensjoner


mm/kg

Rammevariantene nedenfor er et begrenset utvalg. Du kan besøke [roxtec.com](https://www.roxtec.com) for det komplette utvalget av rammer og konfigurasjoner.


| Tittel                        | Rammeåpninger | Fyllplass | Utvendige mål<br>WxHxD | Utsparingsmål<br>w x h      | Vekt | Art.nr. |
|-------------------------------|---------------|-----------|------------------------|-----------------------------|------|---------|
| HD 16 FRAME ASSEMBLY AISI 316 | 1             | 40 x 160  | 83.8 x 236 x 60        | 64(+1/-0.5) x 216(+1/-0.5)  | 1.6  | 193084  |
| HD 32 FRAME ASSEMBLY AISI316  | 2             | 40 x 160  | 130 x 236 x 60         | 110(+1/-0.5) x 216(+1/-0.5) | 2.3  | 109238  |

## Tetningskomponentdata

### Tetningskomponenter



RM BG™-modul med Multidiameter™



RM BG™ blindmodul



smøremiddel

For ytterligere informasjon, kan du besøke [www.roxtec.com](https://www.roxtec.com).



# Forhåndskonfigurerte gjennomføringskit

mm/kg



| Tittel            | Konfigurasjon                  | Utvendige mål<br>WxHxD | Utsparingsmål<br>w x h      | Vekt | Art.nr. |
|-------------------|--------------------------------|------------------------|-----------------------------|------|---------|
| HD 16/4 BG        | 4x (9.5-32.5)                  | 83.8 x 236 x 60        | 64(+1/-0.5) x 216(+1/-0.5)  | 2    | 193105  |
| HD 16/10 BG       | 2x (9.5-32.5), 8x (3.5-16.5)   | 83.8 x 236 x 60        | 64(+1/-0.5) x 216(+1/-0.5)  | 2    | 198299  |
| HD 16/16 BG       | 16x (3.5-16.5)                 | 83.8 x 236 x 60        | 64(+1/-0.5) x 216(+1/-0.5)  | 2    | 193104  |
| HD 32/8 BG B KIT  | 8x (9.5-32.5)                  | 130 x 236 x 60         | 110(+1/-0.5) x 216(+1/-0.5) | 3.3  | 120373  |
| HD 32/32 BG B KIT | 32x (3.5-16.5)                 | 130 x 236 x 60         | 110(+1/-0.5) x 216(+1/-0.5) | 3.5  | 120374  |
| HD 32/20 BG B KIT | 4x (9.5-32.5), 16x (3.5-16.5)  | 130 x 236 x 60         | 110(+1/-0.5) x 216(+1/-0.5) | 3.4  | 120376  |
| HDLC/24+2 BG      | 2x (24.0-54.0), 24x (3.5-16.5) | 378 x 120 x 94         | 366(+1/-1) x 108(+1/-1)     | 5.6  | 173280  |

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2024-04-17