https://www.roxtec.com/linktransit/en-gb/solution/24614







# **Roxtec C KFO transit**

Light-weight cable seal for enclosures

The Roxtec C KFO transit is a cable sealing solution for various kinds of enclosures, where it is important to keep weight down to a minimum. The frame is made of composite (PA) and it is available with a single opening, and with or without flange.





- Rodent resistant
- Light-weight
- Perfect for retrofit
- Easy to maintain and inspect

#### **Product characteristics**



IP/UL NEMA

#### Structure of installation



Cabinets & enclosures

## **Ratings & certificates**

### **Tightness**



IP 55

# **Frame dimensions**

### mm/kg

The frame variants below are a limited selection. For the full range of frames and configurations, please visit roxtec.com.

Product	Frame openings	Packing space	External dimensions WxHxD	Aperture dimensions w x h	Weight	Art. no
C KFO 6x1	1	120 x 180	159 x 260 x 30	123(-2) x 223	0.6	CKF0000060059
C KFO 6x1 WITH FLANGE	1	120 x 180	319 x 420 x 30	170(+5/-5) x 270(+5/-5)	1.4	CKF1000060059
C KFO COUNTER FRAME					0.39	KFC0000100011

# **Sealing components**

### **Sealing components**




C Wedge & C Wedgekit



CM module with Multidiameter™



C Stayplate



CM solid compensation module



Lubricant

For detailed information, please visit roxtec.com.

2024-04-27



#### Read more about the solution on roxtec.com

https://www.roxtec.com/linktransit/en-gb/solution/24614



The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2024-04-27

2/2 2024-04-27