




# Sello Roxtec H3+1 UG™

Sello para cables con entrada a través de la cimentación

El sello Roxtec H3+1 UG™ es ideal para cables de potencia en tresbolillo junto con un cable de tierra de entrada en las cimentaciones y que por tanto, debe funcionar como una barrera duradera contra inundaciones, gas, humedad y roedores. Es un sello dividido en cuatro partes para permitir una fácil instalación y que además, puede instalarse en condiciones de humedad y en entornos con agua circulando. El sello resiste una flexión de cables extrema y ofrece una tolerancia de +3 mm hacia la abertura junto con un indicador que muestra cuándo se ha realizado la compresión correcta del sello. El sello se puede instalar en manguitos pre-rotos, conductos o en agujeros perforados



- Resistente a roedores
- Rápido y sencillo de instalar
- Ofrece una sujeción excelente de los cables

## Características del producto



Estanto al agua



Estanto a gases



IP/UL NEMA

## Estructura de instalación



Hormigón

## Tipo de montaje



Hueco existente



Manguito existente

## Calificaciones y certificados

### Estanquidad

- Gas: 0,3 bar (constante)
- Agua: 0,3 bar (constante)
- IP 68

## Datos de los componentes de sellado

### Componentes de sellado



Sello H3+1 UG™




Lubricante Roxtec

Para obtener información detallada, visite [roxtec.com](https://www.roxtec.com).




# Kits de sellos preconfigurados

mm/kg



H3+1 150 UG



H3+1 200 UG

| Título      | Configuración  | Dimensiones de abertura<br>Ø | Peso | N.º de art. |
|-------------|----------------|------------------------------|------|-------------|
| H3+1 150 UG | 4x (10.0-53.0) | 150 - 153                    | 2.6  | 192261      |
| H3+1 200 UG | 4x (10.0-68.0) | 200 - 203                    | 4.2  | 192082      |

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2024-04-18