



Roxtec

Roxtec RS BG™ 密封系统

用于单根电缆或管道接地的穿隔密封系统。

Roxtec RS BG™ 密封系统适用于单根铠装电缆、金属包覆电缆 或金属管道チ是具有防火和密封性要求的接地应用的理想选择。



防啮齿动物

产品特性









安装结构

金属

安装类型



等级和证书

火灾

● A 级符合 IMO 2010 FTP 规范

密封性

气体: 2 barソ洪灾ゾ

水: 4 barソ洪灾ゾ

支持

● 连接和接地

密封组件数据

密封组件





润滑脂

RS BG™ 密封系统

如需了解详细信息チ请访问 roxtec.com。



预装配的穿隔套件

mm/kg







RS 31 BG AISI316



RS 43 BG AISI316



RS 50 BG AISI316



RS 68 BG AISI316



RS 75 BG AISI316



RS 100 BG AISI316



RS 100 BG AISI316 WOC



RS 125 BG AISI316



RS 125 BG AISI316 woc



RS 150 BG AISI316 woc

| 标题 | 配置 | 开孔尺寸 ∅ | 重量 | 产品编号 |
|-----------------------|-----------------|------------------|------|--------|
| RS 25 BG AISI316 | 1x (3.6-12.0) | 25 - 26 | 0.09 | 164758 |
| RS 31 BG AISI316 | 1x (4.0-17.0) | 31 - 32 | 80.0 | 164773 |
| RS 43 BG AISI316 | 1x (4.0-23.0) | 43 - 45 | 0.26 | 164774 |
| RS 50 BG AISI316 | 1x (8.0-30.0) | 50 - 52 | 0.34 | 125982 |
| RS 68 BG AISI316 | 1x (26.0-48.0) | 68 - 70 | 0.6 | 164776 |
| RS 75 BG AISI316 | 1x (24.0-54.0) | 75 - 77 | 0.7 | 164777 |
| RS 100 BG AISI316 | 1x (48.0-70.0) | 100 - 102 | 1.2 | 164778 |
| RS 100 BG AISI316 WOC | 1x (48.0-70.0) | 100 - 102 | 1 | 182934 |
| RS 125 BG AISI316 | 1x (66.0-98.0) | 125 - 127 | 1.7 | 164779 |
| RS 125 BG AISI316 WOC | 1x (66.0-98.0) | 125 - 127 | 1.5 | 190074 |
| RS 150 BG AISI316 WOC | 1x (93.0-119.0) | 150 - 152 | 1.8 | 164780 |

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales can be downloaded from the products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales can be downloaded from the products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales can be downloaded from the products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales can be downloaded from the products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales can be downloaded from the products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales can be downloaded from the products are offered and sold in accordance with the conditions of the Roxtec Gener

https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/
We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2025-07-03

