



Roxtec SRC r20 GRP - läpivienti

Läpivienti, jossa on lasivahvisteinen polyesterikehys

Roxtec SRC r20 GRP on kaapeliläpivienti, jossa on pyöristetyt kulmat jännityksen ja kehysen rikkoutumisriskin vähentämiseksi. Kehys laminoidaan rakenteeseen ja konfiguroidaan Roxtec RM -moduuleilla, jotka ovat mukautettavissa monen eri halkaisijan kaapeleille. Se voidaan myös konfiguroida tyhjäksi läpivienniksi, joka antaa lisäkapasiteettia tulevia tarpeita varten.



- Kevyt
- Helppo ylläpitää ja tarkistaa

Tuotteen ominaisuudet



Paloluokiteltu



Vesitiivis



Kaasutiivis

Asennusrakenne



Komposiitti

Asennustyyppi



Laminointi

Luokitukset ja sertifiointit

Paloluokka

- A-luokka IMO 2010 -standardin palokoe-koodin (IMO 2010 FTP Code) mukaan

Tiiviyys

- Kaasutiiviyys: 1 bar (katastrofi)
- Vesitiiviyys: 2 bar (katastrofi)

Kehyksen mitat

mm/kg

Alla olevat kehysvaihtoehdot ovat vain osa valikoimastamme. Kattava valikoima kehyksiä ja kokoonpanoja löytyy osoitteesta [roxtec.com](https://www.roxtec.com).


Otsikko	Kehysaukot	Pakkaustila	Ulkomitat WxHxD	Aukon mitat w x h	Paino	Tuotenumero
SRC 4x1 R20 GRP	1	120 x 120	150.5 x 189.5 x 60	156(+3/-3) x 195(+3/-3)	0.9	198826
SRC 6x1 R20 GRP	1	120 x 180	150.5 x 248 x 60	156(+3/-3) x 254(+3/-3)	1	198827

Tiivistyskomponenttien tiedot

Tiivistyskomponentit




Roxtec-asennusrasva




RM -moduuli
Multidiameter™-teknologialla



Wedge ja Wedgekit



RM -umpimoduuli



Roxtec-välilevy

Lisätietoja on osoitteessa [roxtec.com](https://www.roxtec.com).



The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2024-04-27