



# Roxtec TB seal with SL TB

Round penetration seal for a single cable or pipe in steel tank boundary structures.

The Roxtec TB (tank boundary) with SL TB is a round seal with a steel sleeve for a single cable or pipe. The entry seal has two halves with removable rubber layers making it adaptable to cables and pipes of different sizes. The front fittings ensure mechanical anchorage in the sleeve. The SL TB sleeve is welded to the structure.

- Quick and easy to install
- Adapts to cables and pipes of different sizes



Mounting type

Welding

### Product characteristics

Watertight





#### Structure of installation



## **Ratings & certificates**

#### Fire

A-CLASS according to IMO 2010 FTP Code

#### Tightness

- Gas: 2 bar (catastrophic) / 1.2 bar (tank boundaries)
- Water: 11 bar (catastrophic) / 6.6 bar (tank boundaries)

### **Sealing components**

#### Sealing components



Lubricant



For detailed information, please visit roxtec.com.





## **Pre-configured transit kits**

mm/kg



TB 65 KIT AISI316 WOC/PRIMED



TB 65 KIT AISI316 WOC/AISI316

TB 105 KIT AISI316 WOC/PRIMED



TB 105 KIT AISI316 /AISI316

| 20 | WUC/A |  |  |
|----|-------|--|--|
|    |       |  |  |
|    |       |  |  |

| Product                        | Configuration  | Aperture dimensions<br>Ø | Weight | Art. no |
|--------------------------------|----------------|--------------------------|--------|---------|
| TB 65 KIT AISI316 WOC/PRIMED   | 1x (8.0-30.0)  | 80 - 82                  | 1.6    | 184905  |
| TB 65 KIT AISI316 WOC/AISI316  | 1x (8.0-30.0)  | 80 - 82                  | 1.6    | 196482  |
| TB 105 KIT AISI316 WOC/PRIMED  | 1x (24.0-54.0) | 120 - 122                | 2.8    | 200102  |
| TB 105 KIT AISI316 WOC/AISI316 | 1x (24.0-54.0) | 120 - 122                | 2.9    | 200103  |

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for

Reproduct any owner of the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system was designed or intended. Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, contraction and and a sumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect,

consequential, punitive, special, exemplary or incidental damages or losses. The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/ We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright. This document was generated on: 2024-05-03