



Soluția Roxtec TB cu manșon SL TB

Soluție rotundă pentru etanșarea unui cablu sau unei țevi în structura rezervoarelor metalice.

Soluția Roxtec TB (tank boundary) cu manșonul SL TB este o etanșare rotundă pentru un cablu sau o țevă. Etanșarea are două jumătăți cu straturi de cauciuc detașabile, fiind astfel adaptabilă la un cablu sau o țevă de diferite dimensiuni. Fitingurile frontale asigură ancorarea mecanică în manșon. Manșonul SL TB este sudat la structură.

- Rapid și ușor de instalat
- Se adaptează la cabluri și țevi de diferite dimensiuni



Caracteristicile produsului



Certificată la foc



Etanșă la apă



Etanșă la gaze

Structura instalației



Metal

Tip de montaj



Sudare

Clase și certificate

Foc

- CLASA A conform Codului FTP IMO 2010

Etanșeitate

- Gaz: 2 bari (catastrofică) / 1,2 bari (pereții rezervorului)
- Apă: 11 bari (catastrofică) / 6,6 bari (pereții rezervorului)

Date componente de etanșare

Componente de etanșare



Lubrifiant Roxtec



Soluția completă TB

Pentru mai multe informații, vă rugăm să vizitați [roxtec.com](https://www.roxtec.com).



Kituri de treceri preconfigurate


mm/kg




TB 65 KIT AISI316
WOC/AISI316



TB 65 KIT AISI316
WOC/PRIMED



TB 105 KIT AISI316
WOC/AISI316



TB 105 KIT AISI316
WOC/PRIMED

Titlu	Configurație	Dimensiuni deschidere Ø	Greutate	Nr. art.
TB 65 KIT AISI316 WOC/AISI316	1x (8.0-30.0)	80 - 82	1.6	196482
TB 65 KIT AISI316 WOC/PRIMED	1x (8.0-30.0)	80 - 82	1.6	184905
TB 105 KIT AISI316 WOC/AISI316	1x (24.0-54.0)	120 - 122	2.9	200103
TB 105 KIT AISI316 WOC/PRIMED	1x (24.0-54.0)	120 - 122	2.8	200102

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2024-04-27