



Roxtec TB-tätning med SL TB-hylsa

Rund genomförelstättning för enstaka kablar eller rör i konstruktioner som avgränsar ståltankar.

Roxtec TB (tank boundary) med SL TB är en rund tätning med en stålhylsa för enstaka kablar eller rör. Tätningen har två halvor med avskalbara gummilager som gör den anpassningsbar till kablar och rör av olika dimensioner. Frontbeslagen säkerställer den mekaniska förankringen i hylsan. SL TB-hylsan svetsas fast i strukturen.

- Snabb och enkel installation
- Anpassningsbar till kablar och rör med olika dimensioner



Produktegenskaper



Brandklassad



Vattentät



Gastät

Konstruktion för installation



Metall

Monteringsätt



Svetsning

Klassningar & certifikat

Brand

- A-KLASS enligt IMO 2010 FTP-kod

Täthet

- Gas: 2 bar (katastrofmässigt) / 1,2 bar (tankväggar)
- Vatten: 11 bar (katastrofmässigt) / 6,6 bar (tankväggar)

Information om tätningskomponenter

Tätningskomponenter



smörjmedel



TB-kit

Detaljerad information finns på [roxtec.com](https://www.roxtec.com).



Förkonfigurerade genomföringskit


mm/kg




TB 65 KIT AISI316
WOC/AISI316



TB 65 KIT AISI316
WOC/PRIMED



TB 105 KIT AISI316
WOC/AISI316



TB 105 KIT AISI316
WOC/PRIMED

Titel	Konfigurering	Öppningens mått Ø	Vikt	Art. nr
TB 65 KIT AISI316 WOC/AISI316	1x (8.0-30.0)	80 - 82	1.6	196482
TB 65 KIT AISI316 WOC/PRIMED	1x (8.0-30.0)	80 - 82	1.6	184905
TB 105 KIT AISI316 WOC/AISI316	1x (24.0-54.0)	120 - 122	2.9	200103
TB 105 KIT AISI316 WOC/PRIMED	1x (24.0-54.0)	120 - 122	2.8	200102

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use. Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended. Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses. The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/> We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright. This document was generated on: 2024-04-27