



Roxtec C LH 貫通部

構造にボルトで固定するタイプの軽量型貫通

Roxtec C LH

は、コンパクトかつ軽量のデザインでありながら、複数のケーブルやパイプが貫通する開口部に強力に密閉するソリューションです。5つのサイズから選べます。貫通部フレームはアルミニウム製で、ボルトで構造物に取り付けるタイプです。シーリングモジュールは異なる外径のケーブルやパイプに対応でき、将来の更新や増設工事で使用できる予備スペースを貫通部に確保しておくことを可能にします。鉄道車両などのモビリティ分野における用途に最適で、壁や床に設けた貫通部から水や塵埃が侵入するのを防ぎ、耐火、防振、ケーブル把持に優れています。



- 軽量
- 優れた面積効率
- 予備スペースの確保

製品特性



耐火



IP/UL NEMA

設置構造



キャビネット & エンクロージング



金属

取り付けタイプ



ボルト締め

規格と認証証明書

火災

- EN 45545 E30 に基づく試験で E/EI 等級

密性

- IP 66

フレーム寸法

mm/kg


以下のフレームは一部です。フレームと構成品の全ラインナップについては、[roxtec.com](https://www.roxtec.com) をご覧ください。

タイトル	フレームの開口部	パッキンスペース	外径 WxHxD	開口部寸法 w x h	重量	部品番号
C LH 3x1 ALU	1	60 x 120	120.2 x 218.5 x 30	76(+1/-1) x 174.5(+1/-1)	0.6	234431
C LH 4x1 ALU	1	120 x 120	180.2 x 218.5 x 30	136(+1/-1) x 174.5(+1/-1)	0.5	234434
C LH 5x1 ALU	1	60 x 180	120.2 x 276.5 x 30	76(+1/-1) x 232.5(+1/-1)	0.5	234432
C LH 6x1 ALU	1	120 x 180	180.2 x 276.5 x 30	136(+1/-1) x 232.5(+1/-1)	0.6	234435
C LH 7x1 ALU	1	60 x 240	120.2 x 336.5 x 30	76(+1/-1) x 292.5(+1/-1)	0.6	234433



シーリングコンポーネントのデータ


シーリングコンポーネント



Multidiamer™ 付き CM



C ステーププレート



CM ソリッドコンペ
ンセーションモジュール




Lubricant



C ウェッジおよびウ



ホルダー・ツール



Multidiamer™ 付き CM
PPS モジュール

詳細情報については、[roxtec.com](https://www.roxtec.com) をご覧ください。

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2024-09-27