



Roxtec LabSeal™ C LTX

Rengøringsvenlig gennemføring til laboratorier og renrum.

Roxtec LabSeal™ er optimeret til kabel- og rørgennemføringer i lufttætte faciliteter som f.eks. laboratorier og renrum. Den er hygiejnisk designet med en rengøringsvenlig pulverlakeret aluminiumsramme og en glat overflade med drænbare kanter, integrerede kompressionsenheder og skjulte monteringskruer. Den lette og pladsbesparende gennemføring er nem at installere. Det sikrer en lufttæt forsegling, når det fastgøres til væggen eller loftet og giver ekstra kapacitet til fremtidige opgraderinger.



- Hurtig og nem at montere
- Nem at vedligeholde og inspicere
- Har indbygget reservekapacitet
- Modulært design

Produktegenskaber



Brandklassificeret



IP/UL NEMA

Byggekonstruktion



Sandwich panel



Gips

Monteringstype



Bolting

Normeringer og certifikater

Brand

- E/EI-klassificering i henhold til EN 13501

Tæthed

- IP 66/67 i henhold til IEC 60529

Rammedimensioner


mm/kg

De nedenstående rammevarianter udgør et begrænset udvalg. Du kan se hele udvalget af rammer og konfigurationer på [roxtec.com](https://www.roxtec.com).

Title	Rammeåbninger	Pakkeareaö	Udvendige mål WxHxD	Åbningsmål w x h	Vægt	Art.-nr.
LABSEAL C LTX WITH COUNTER FRAME 0-40	2	60 x 180	201 x 296 x 86	165(+2/-1) x 261(+2/-1)	2.9	241407
LABSEAL C LTX WITH EXT. FRAME 90-100	2	60 x 180	201 x 296 x 146	165(+2/-1) x 261(+2/-1)	3.5	244894

Data om tætningskomponenter

Tætningskomponenter



CM-modul med Multidiameter™

For merne information, besøg venligst [roxtec.com](https://www.roxtec.com).



Foreslåede tætningskit

mm/kg



Title	Konfiguration	Udvendige mål WxHxD	Åbningsmål w x h	Vægt	Art.-nr.
LABSEAL C LTX/6	6x (24.0-54.0)	201 x 296 x 146	165(+2/-1) x 261(+2/-1)	4.5	246143
LABSEAL C LTX/15	12x (10.0-25.0), 3x (24.0-54.0)	201 x 296 x 146	165(+2/-1) x 261(+2/-1)	4.5	246142
LABSEAL C LTX/24	24x (10.0-25.0)	201 x 296 x 146	165(+2/-1) x 261(+2/-1)	4.5	246141

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2025-12-01