



# Roxtec LabSeal™ C LTX

Easy-to-clean transit for labs and cleanrooms.

The Roxtec LabSeal™ is optimized for cable and pipe penetrations in airtight facilities such as laboratories and cleanrooms. It is hygienically designed with an easy-to-clean powder-coated aluminum frame and a smooth surface with drainable edges, integrated compression units and hidden mounting screws. The lightweight and area efficient transit is easy to install. It ensures an airtight seal when attached to the wall or ceiling and provides spare capacity for future upgrades.



- Quick and easy to install
- Easy to maintain and inspect
- Provides built-in spare capacity
- Modular design

## Product characteristics



Fire rated



IP/UL NEMA

## Structure of installation



Sandwich panel



Gypsum

## Mounting type



Bolting

## Ratings & certificates

### Fire

- E/EI rating according to EN 13501

### Tightness

- IP 66/67 according to IEC 60529

## Frame dimensions


mm/kg

The frame variants below are a limited selection. For the full range of frames and configurations, please visit [roxtec.com](https://www.roxtec.com).

| Product                                  | Frame openings | Packing space | External dimensions<br>WxHxD | Aperture dimensions<br>w x h | Weight | Art. no |
|------------------------------------------|----------------|---------------|------------------------------|------------------------------|--------|---------|
| LABSEAL C LTX WITH<br>COUNTER FRAME 0-40 | 2              | 60 x 180      | 201 x 296 x 86               | 165(+2/-1) x 261(+2/-1)      | 2.9    | 241407  |
| LABSEAL C LTX WITH EXT.<br>FRAME 90-100  | 2              | 60 x 180      | 201 x 296 x 146              | 165(+2/-1) x 261(+2/-1)      | 3.5    | 244894  |

## Sealing components

### Sealing components



CM module with Multidiameter™

For detailed information, please visit [roxtec.com](https://www.roxtec.com).



# Pre-configured transit kits

mm/kg



| Product          | Configuration                   | External dimensions<br>WxHxD | Aperture dimensions<br>w x h | Weight | Art. no |
|------------------|---------------------------------|------------------------------|------------------------------|--------|---------|
| LABSEAL C LTX/6  | 6x (24.0-54.0)                  | 201 x 296 x 146              | 165(+2/-1) x 261(+2/-1)      | 4.5    | 246143  |
| LABSEAL C LTX/15 | 12x (10.0-25.0), 3x (24.0-54.0) | 201 x 296 x 146              | 165(+2/-1) x 261(+2/-1)      | 4.5    | 246142  |
| LABSEAL C LTX/24 | 24x (10.0-25.0)                 | 201 x 296 x 146              | 165(+2/-1) x 261(+2/-1)      | 4.5    | 246141  |

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2025-12-01