



Roxtec LabSeal™ C LTX

Sello fácil de limpiar para laboratorios y salas limpias.

El LabSeal™ de Roxtec está optimizado para las entradas de cables y tuberías en instalaciones estancas como laboratorios y salas limpias. Tiene un diseño higiénico con un marco de aluminio con recubrimiento en polvo fácil de limpiar y una superficie lisa con bordes drenables, unidades de compresión integradas y tornillos de montaje ocultos. El sello es ligero y con una buena eficiencia de área y es fácil de instalar. Garantiza un sellado hermético cuando se fija a la pared o al techo y proporciona capacidad de reserva para futuras expansiones o modificaciones.



- Rápido y sencillo de instalar
- Fácil de mantener e inspeccionar
- Ofrece capacidad de repuesto incorporada
- Diseño modular

Características del producto



Calificación
contra incendios



IP/UL NEMA

Estructura de instalación



Panel
sándwich



Yeso

Tipo de montaje



Atornilladura

Calificaciones y certificados

Fuego

- Clasificación E/EI según EN 13501

Estanquidad

- IP 66/67 según IEC 60529

Dimensiones del marco


mm/kg

Las variantes de marcos que figuran a continuación son una selección limitada. Para ver la gama completa de marcos y configuraciones, visite [roxtec.com](https://www.roxtec.com).

Título	Aperturas de marcos	Espacio útil de sellado	Dimensiones externas WxHxD	Dimensiones de abertura w x h	Peso	N.º de art.
LABSEAL C LTX WITH COUNTER FRAME 0-40	2	60 x 180	201 x 296 x 86	165(+2/-1) x 261(+2/-1)	2.9	241407
LABSEAL C LTX WITH EXT. FRAME 90-100	2	60 x 180	201 x 296 x 146	165(+2/-1) x 261(+2/-1)	3.5	244894

Datos de los componentes de sellado

Componentes de sellado



Módulo CM con Multidiameter™

Para obtener información detallada, visite [roxtec.com](https://www.roxtec.com).

Kits de sellos preconfigurados

mm/kg



Título	Configuración	Dimensiones externas WxHxD	Dimensiones de abertura w x h	Peso	N.º de art.
LABSEAL C LTX/6	6x (24.0-54.0)	201 x 296 x 146	165(+2/-1) x 261(+2/-1)	4.5	246143
LABSEAL C LTX/15	12x (10.0-25.0), 3x (24.0-54.0)	201 x 296 x 146	165(+2/-1) x 261(+2/-1)	4.5	246142
LABSEAL C LTX/24	24x (10.0-25.0)	201 x 296 x 146	165(+2/-1) x 261(+2/-1)	4.5	246141

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2025-12-01