



Roxtec LabSeal™ C LTX

Helposti puhdistettava läpivienti laboratorioihin ja puhdastiloihin.

Roxtec LabSeal™ on optimoitu kaapeleiden ja putkien läpivienneille ilmatiiviissä tiloissa, kuten laboratorioissa ja puhdastiloissa.

Se on hygieenisesti suunniteltu, ja siinä on helposti puhdistettava, jauhemaalattu sileäpintainen alumiinirunko. Läpivientikehys on varustettu kallistetuilla, vedenpoiston mahdollistavilla tyhjennysreunoilla, integroiduilla puristussyksiköillä ja piilotetuilla kiinnitysruuveilla.

Kevyt ja pinta-alatehokas läpivienti on helppo asentaa. Se varmistaa ilmatiiviin tiivistyksen seinään tai kattoon kiinnitettynä ja tarjoaa ylimääräistä kapasiteettia tulevia päivityksiä varten.



- Helppo ja nopea asennus
- Helppo ylläpitää ja tarkistaa
- Sisäänrakennettu lisäkapasiteetti
- Modulaarinen muotoilu

Tuotteen ominaisuudet



Paloluokiteltu



IP/UL NEMA

Asennusrakenne



Sandwich-paneeli



Kipsi

Asennustyyppi



Pulttaus

Luokitukset ja sertifiointit

Paloluokka

- E/EI-luokitus standardin EN 13501 mukaan

Tiiviys

- IP 66/67 standardin IEC 60529 mukaan

Kehyksen mitat


mm/kg

Alla olevat kehysvaihtoehdot ovat vain osa valikoimastamme. Kattava valikoima kehyksiä ja kokoonpanoja löytyy osoitteesta [roxtec.com](https://www.roxtec.com).

Otsikko	Kehysaukot	Pakkaustila	Ulkomitat WxHxD	Aukon mitat w x h	Paino	Tuotenro
LABSEAL C LTX WITH COUNTER FRAME 0-40	2	60 x 180	201 x 296 x 86	165(+2/-1) x 261(+2/-1)	2.9	241407
LABSEAL C LTX WITH EXT. FRAME 90-100	2	60 x 180	201 x 296 x 146	165(+2/-1) x 261(+2/-1)	3.5	244894

Tiivistyskomponenttien tiedot

Tiivistyskomponentit



CM -moduuli
Multidiameter™-teknologialla

Lisätietoja on osoitteesta [roxtec.com](https://www.roxtec.com).

Valmiiksi määritetyt läpivientisarjat

mm/kg



Otsikko	Kokoonpano	Ulkomitat WxHxD	Aukon mitat w x h	Paino	Tuotenro
LABSEAL C LTX/6	6x (24.0-54.0)	201 x 296 x 146	165(+2/-1) x 261(+2/-1)	4.5	246143
LABSEAL C LTX/15	12x (10.0-25.0), 3x (24.0-54.0)	201 x 296 x 146	165(+2/-1) x 261(+2/-1)	4.5	246142
LABSEAL C LTX/24	24x (10.0-25.0)	201 x 296 x 146	165(+2/-1) x 261(+2/-1)	4.5	246141

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2025-12-01