



Roxtec LabSeal™ C LTX

Trasporto facile da pulire per laboratori e camere bianche.

Roxtec LabSeal™ è ottimizzato per l'attraversamento di cavi e tubi in strutture a tenuta d'aria come laboratori e camere bianche. È progettato igienicamente con un telaio in alluminio verniciato a polvere facile da pulire e una superficie liscia con bordi drenabili, unità di compressione integrate e viti di montaggio nascoste. Il transito leggero ed efficiente nello spazio è facile da installare. Garantisce una tenuta ermetica quando è fissato alla parete o al soffitto e fornisce capacità di riserva per futuri aggiornamenti.



- Veloce e facile da installare
- Facilità di manutenzione e controllo
- Consente capacità di riserva integrata
- Design modulare

Caratteristiche



Resistenza al fuoco



IP/UL NEMA

Struttura dell'installazione



Pannello sandwich



Gesso

Tipo di montaggio



Imbullonatura

Ratings e certificati

Fuoco

- Classificazione E/EI secondo EN 13501

Tenuta

- IP 66/67 in accordo a IEC 60529

Dimensioni telaio


mm/kg

Le varianti di telaio seguenti rappresentano una selezione limitata. Per la gamma completa di telai e configurazioni, visita [roxtec.com](https://www.roxtec.com).

Titolo	Aperture del telaio	Spazio di riempimento	Dimensioni esterne WxHxD	Dimensioni apertura w x h	Peso	Art. Nr.
LABSEAL C LTX WITH COUNTER FRAME 0-40	2	60 x 180	201 x 296 x 86	165(+2/-1) x 261(+2/-1)	2.9	241407
LABSEAL C LTX WITH EXT. FRAME 90-100	2	60 x 180	201 x 296 x 146	165(+2/-1) x 261(+2/-1)	3.5	244894

Dati relativi ai componenti

Componenti per la sigillatura



Modulo CM con Multidiameter™

Per informazioni dettagliate, visita la pagina [roxtec.com](https://www.roxtec.com).

Kit pre-configurati

mm/kg



Titolo	Configurazione	Dimensioni esterne WxHxD	Dimensioni apertura w x h	Peso	Art. Nr.
LABSEAL C LTX/6	6x (24.0-54.0)	201 x 296 x 146	165(+2/-1) x 261(+2/-1)	4.5	246143
LABSEAL C LTX/15	12x (10.0-25.0), 3x (24.0-54.0)	201 x 296 x 146	165(+2/-1) x 261(+2/-1)	4.5	246142
LABSEAL C LTX/24	24x (10.0-25.0)	201 x 296 x 146	165(+2/-1) x 261(+2/-1)	4.5	246141

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2025-12-01