



Roxtec LabSeal™ C LTX

Gjennomføring som er enkel å rengjøre, for laboratorier og renrom.

Roxtec LabSeal™ er optimalisert for kabel- og rørgjennomføringer i lufttette anlegg som laboratorier og renrom. Den er hygienisk utformet med en pulverlakkert aluminiumsramme som er lett å rengjøre og en glatt overflate med drenerbare kanter, integrerte kompresjonsenheter og skjulte monteringskruer. Den lette og arealbesparende gjennomføringen er enkel å installere. Den sikrer en lufttett forsegling når den festes til veggen eller taket, og gir ekstra kapasitet for fremtidige oppgraderinger.



- Rask og enkel å installere
- Enkel å vedlikeholde og inspisere
- Gir innebygd reservekapasitet
- Modulær utforming

Produktegenskaper



Brannklassifisert



IP/UL NEMA

Struktur for installasjon



Sandwich-p
anel



Gips

Festetype



Bolting

Graderinger og sertifikater

Brann

- E/EI-klassifisering i henhold til EN 13501

Tetthet

- IP 66/67 i henhold til IEC 60529

Rammedimensjoner


mm/kg

Rammevariantene nedenfor er et begrenset utvalg. Du kan besøke [roxtec.com](https://www.roxtec.com) for det komplette utvalget av rammer og konfigurasjoner.

Tittel	Rammeåpninger	Fyllplass	Utvendige mål WxHxD	Utsparingsmål w x h	Vekt	Art.nr.
LABSEAL C LTX WITH COUNTER FRAME 0-40	2	60 x 180	201 x 296 x 86	165(+2/-1) x 261(+2/-1)	2.9	241407
LABSEAL C LTX WITH EXT. FRAME 90-100	2	60 x 180	201 x 296 x 146	165(+2/-1) x 261(+2/-1)	3.5	244894

Tetningskomponentdata

Tetningskomponenter



CM-modul med Multidiameter™

For ytterligere informasjon, kan du besøke www.roxtec.com.



Forhåndskonfigurerte gjennomføringskit

mm/kg



Tittel	Konfigurasjon	Utvendige mål WxHxD	Utsparingsmål w x h	Vekt	Art.nr.
LABSEAL C LTX/6	6x (24.0-54.0)	201 x 296 x 146	165(+2/-1) x 261(+2/-1)	4.5	246143
LABSEAL C LTX/15	12x (10.0-25.0), 3x (24.0-54.0)	201 x 296 x 146	165(+2/-1) x 261(+2/-1)	4.5	246142
LABSEAL C LTX/24	24x (10.0-25.0)	201 x 296 x 146	165(+2/-1) x 261(+2/-1)	4.5	246141

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2025-12-01