



Roxtec LabSeal™ C LTX

Eenvoudig te reinigen doorvoer voor laboratoria en cleanrooms.

De Roxtec LabSeal™ is geoptimaliseerd voor kabel- en leidingdoorvoeringen in luchtdichte faciliteiten, zoals laboratoria en cleanrooms. De doorvoer is hygiënisch ontworpen met een eenvoudig te reinigen, gepoedercoat aluminium frame en een glad oppervlak met aflopende randen, geïntegreerde compressie-units en weggewerkte bevestigingsbouten. De lichtgewicht en ruimtebesparende doorvoer is eenvoudig te installeren. De doorvoer wordt in de wand of het plafond bevestigd, zorgt voor een luchtdichte afdichting en biedt reservecapaciteit voor toekomstige upgrades.



- Snel en eenvoudig te installeren
- Eenvoudig te onderhouden en inspecteren
- Biedt ingebouwde reservecapaciteit
- Modulair ontwerp

Producteigenschappen



Brandvertragend



IP/UL NEMA

Installatiestructuur



Sandwichpaneel



Gips

Montagetype



Bouten

Specificaties en certificaten

Brand

- E/EI-classificatie volgens EN 13501

Dichtheid

- IP 66/67 conform IEC 60529

Afmetingen frame


mm/kg

De onderstaande frame-uitvoeringen zijn een beperkte selectie. Ga naar [roxtec.com](https://www.roxtec.com) voor het volledige assortiment frames en configuraties.

Titel	Frame-openingen	Vrije doorvoerruimte	Buitenafmetingen WxHxD	Afmetingen opening w x h	Gewicht	Art. nr.
LABSEAL C LTX WITH COUNTER FRAME 0-40	2	60 x 180	201 x 296 x 86	165(+2/-1) x 261(+2/-1)	2.9	241407
LABSEAL C LTX WITH EXT. FRAME 90-100	2	60 x 180	201 x 296 x 146	165(+2/-1) x 261(+2/-1)	3.5	244894

Gegevens van afdichtcomponenten

Afdichtcomponenten



CM module met Multidiameter™

Ga naar [roxtec.com](https://www.roxtec.com) voor uitgebreide informatie.



Vooraf geconfigureerde doorvoersets

mm/kg



Titel	Configuratie	Buitenafmetingen WxHxD	Afmetingen opening w x h	Gewicht	Art. nr.
LABSEAL C LTX/6	6x (24.0-54.0)	201 x 296 x 146	165(+2/-1) x 261(+2/-1)	4.5	246143
LABSEAL C LTX/15	12x (10.0-25.0), 3x (24.0-54.0)	201 x 296 x 146	165(+2/-1) x 261(+2/-1)	4.5	246142
LABSEAL C LTX/24	24x (10.0-25.0)	201 x 296 x 146	165(+2/-1) x 261(+2/-1)	4.5	246141

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2025-12-01