



Roxtec LabSeal™ C LTX

Laboratuvarlar ve temiz odalar için temizlemesi kolay geçiş.

Roxtec LabSeal™, laboratuvarlar ve temiz odalar gibi hava geçirmez tesislerde kablo ve boru geçişleri için optimize edilmiştir. Temizlemesi kolay toz boyalı alüminyum çerçeve ve boşaltılabilir kenarlara sahip pürüzsüz bir yüzey, entegre sıkıştırma üniteleri ve gizli montaj vidaları ile hijyenik olarak tasarlanmıştır. Hafif ve alan açısından verimli geçiş düzeneğinin kurulumu kolaydır. Duvara veya tavana takıldığında hava geçirmez bir sızdırmazlık sağlar ve gelecekteki yükseltmeler için yedek kapasite sağlar.



- Hızlı ve kolay montaj
- Kolay bakım ve denetim
- Dahili yedek kapasite sağlar
- Modüler tasarım

Ürün özellikleri



Yangın sınıflamalı



IP/UL NEMA

Montaj yapılacak yapı



Sandviç panel



Alçı

Montaj tipi



Cıvatalama

Derecelendirmeler ve sertifikalar

Yangın

- EN 13501 standardına göre E/EI derecesi

Sızdırmazlık

- IEC 60529'a göre IP 66/67

Çerçeve boyutları


mm/kg

Aşağıdaki çerçeve çeşitleri sınırlı sayıda seçenekten oluşmaktadır. Çerçeve ve yapılandırma yelpazesinin tamamı için [roxtec.com](https://www.roxtec.com) adresini ziyaret edin.

Başlık	Çerçeve açıklıkları	Modül koyulan alan	Dış boyutlar WxHxD	Açıklık boyutları w x h	Ağırlık	Madde Numarası
LABSEAL C LTX WITH COUNTER FRAME 0-40	2	60 x 180	201 x 296 x 86	165(+2/-1) x 261(+2/-1)	2.9	241407
LABSEAL C LTX WITH EXT. FRAME 90-100	2	60 x 180	201 x 296 x 146	165(+2/-1) x 261(+2/-1)	3.5	244894

Yalıtım elemanı verileri

Yalıtım elemanları



Multidiameter™ özellikli CM modül

Ayrıntılı bilgi için lütfen [roxtec.com](https://www.roxtec.com) adresini ziyaret edin.



Önceden yapılandırılmış geçiş kitleri

mm/kg



LABSEAL C LTX/6



LABSEAL C LTX/15



LABSEAL C LTX/24

Başlık	Konfigürasyon	Dış boyutlar WxHxD	Açıklık boyutları w x h	Ağırlık	Madde Numarası
LABSEAL C LTX/6	6x (24.0-54.0)	201 x 296 x 146	165(+2/-1) x 261(+2/-1)	4.5	246143
LABSEAL C LTX/15	12x (10.0-25.0), 3x (24.0-54.0)	201 x 296 x 146	165(+2/-1) x 261(+2/-1)	4.5	246142
LABSEAL C LTX/24	24x (10.0-25.0)	201 x 296 x 146	165(+2/-1) x 261(+2/-1)	4.5	246141

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2025-12-01



Roxtec ® and Multidiameter ® are registered trademarks of Roxtec in Sweden and/or other countries.