



# Roxtec CSP transits

Cabinet seal for high cable density applications.

The Roxtec CSP 16/32 is a multi-cable and pipe transit device for cabinets and enclosures. The frame is made of acid proof stainless steel and available in sizes for up to 16 or 32 cables. It has an integrated compression unit to further enhance usability and ease of installation. The sealing modules adapt to cables and pipes of different sizes and can be chosen in line with specific needs for IP or UL/NEMA ratings.



- Area efficient
- Quick and easy to install
- Allows pre-terminated cables

## Product characteristics



IP/UL NEMA

## Structure of installation



Cabinets & enclosures



Metal

## Mounting type



Bolting

## Ratings & certificates

### Tightness

- IP 66/67 according to IEC 60529, UL/NEMA 4,4X,12,13

## Frame dimensions


### in/lbs

The frame variants below are a limited selection. For the full range of frames and configurations, please visit [roxtec.com](https://www.roxtec.com).


| Product                       | Frame openings | Packing space | External dimensions<br>WxHxD | Aperture dimensions<br>w x h                 | Weight | Art. no |
|-------------------------------|----------------|---------------|------------------------------|----------------------------------------------|--------|---------|
| CSP 16 AISI316 FRAME ASSEMBLY | 2              | 1.575 x 3.15  | 5.157 x 5.512 x 2.5          | 4.291(+0.039/-0.02) x<br>4.291(+0.039/-0.02) | 3.97   | 233728  |
| CSP 32 AISI316 FRAME ASSEMBLY | 4              | 1.575 x 3.15  | 8.78 x 5.512 x 2.5           | 7.913(+0.039/-0.02) x<br>4.291(+0.039/-0.02) | 6.33   | 233729  |

## Sealing components

### Sealing components



HD module with Multidiameter™



HD solid compensation module



Lubricant

For detailed information, please visit [roxtec.com](https://www.roxtec.com).



# Pre-configured transit kits

in/lbs



| Product   | Configuration                                          | External dimensions<br>WxHxD | Aperture dimensions<br>w x h | Weight | Art. no |
|-----------|--------------------------------------------------------|------------------------------|------------------------------|--------|---------|
| CSP 16/4  | 4x (0.374-1.240)                                       | 5.157 x 5.512 x 2.5          | 4.291 x 4.291                | 4.74   | 241194  |
| CSP 32/8  | 8x (0.374-1.240)                                       | 8.78 x 5.512 x 2.5           | 7.913 x 4.291                | 8.16   | 241713  |
| CSP 16/10 | 2x (0.374-1.240), 8x (0.138-0.610)                     | 5.157 x 5.512 x 2.5          | 4.291 x 4.291                | 4.63   | 241193  |
| CSP 32/20 | 4x (0.374-1.240), 16x (0.138-0.610)                    | 8.78 x 5.512 x 2.5           | 7.913 x 4.291                | 8.09   | 241717  |
| CSP 16/16 | 16x (0.138-0.610)                                      | 5.157 x 5.512 x 2.5          | 4.291 x 4.291                | 4.63   | 241192  |
| CSP 32/32 | 32x (0.138-0.610)                                      | 8.78 x 5.512 x 2.5           | 7.913 x 4.291                | 8.02   | 241716  |
| CSP 32/41 | 1x (0.374-1.240), 16x (0.138-0.610), 24x (0.138-0.374) | 8.78 x 5.512 x 2.5           | 7.913 x 4.291                | 8.14   | 241718  |

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2026-08-05