



Roxtec CSP 트랜짓

고밀도 케이블 환경을 위한 캐비닛 쉴.

Roxtec CSP 16/32는 캐비닛 및 인클로저용 트랜짓입니다. 프레임은 AISI316 스테인리스 스틸로 만들어졌으며, 최대 16개 또는 32개의 케이블을 수용할 수 있는 규격으로 제공됩니다. 프레임에는 사용성과 설치 편의성을 더욱 높여주는 통합 압축 장치가 적용되어 있습니다. 쉴링 모듈은 다양한 사이즈의 케이블 및 파이프에 적용되며, IP 또는 UL/NEMA 등급의 특정 요구 사항에 따라 선택할 수 있습니다.



- 공간 효율성
- 빠르고 간편한 설치
- 중단 케이블 허용

제품 특징점



IP/UL NEMA

설치 구조



캐비닛 및 인클로저



금속

장착 유형



볼트체결

등급 및 인증

강도

- IEC 60529에 따른 IP 66/67, UL/NEMA 4,4X,12,13

프레임 치수

mm/kg

아래의 프레임 변화는 제한된 선택입니다. 프레임 및 구성의 전체 범위를 보려면 [roxtec.com](https://www.roxtec.com)을 방문하십시오.


구성	프레임 입구	모듈설치공간	외부 치수 WxHxD	홀 치수 w x h	무게	Art. 번호
CSP 32 AISI316 FRAME ASSEMBLY	4	40 x 80	223 x 140 x 63.5	201 x 109	2.9	233729
CSP 16 AISI316 FRAME ASSEMBLY	2	40 x 80	131 x 140 x 63.5	109(+1/-0.5) x 109(+1/-0.5)	1.8	233728

쉴링 컴포넌트 데이터


쉴링 컴포넌트



윤활제



HD 모듈(Multidiameter™)



HD 솔리드 모듈

자세한 내용은 [roxtec.com](https://www.roxtec.com)을 방문하십시오.



키트 구성의 관통장비

mm/kg



구성	구성	외부 치수 WxHxD	홀 치수 w x h	무게	Art. 번호
CSP 32/8	8x (9.5-31.5)	223 x 140 x 63.5	201 x 109	3.1	241713
CSP 16/4	4x (9.5-31.5)	131 x 140 x 63.5	109 x 109	1.8	241194
CSP 16/16	16x (3.5-15.5)	131 x 140 x 63.5	109 x 109	2.1	241192
CSP 32/32	32x (3.5-15.5)	223 x 140 x 63.5	201 x 109	3.6	241716
CSP 32/41	1x (9.5-31.5), 16x (3.5-15.5), 24x (3.5-9.5)	223 x 140 x 63.5	201 x 109	3.1	241718
CSP 32/20	4x (9.5-31.5), 16x (3.5-15.5)	223 x 140 x 63.5	201 x 109	3.7	241717
CSP 16/10	2x (9.5-31.5), 8x (3.5-15.5)	131 x 140 x 63.5	109 x 109	2.1	241193

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2025-12-12

