



Roxtec CSP-gjennomføringer

Tetningsløsning for skap med høy kabeltetthet.

Roxtec CSP 16/32 er en gjennomføringsløsning for flere kabler og rør, utviklet for skap og kapslinger. Rammen er laget av AISI316 rustfritt stål og finnes i størrelser for opptil 16 eller 32 kabler. Den har en integrert kompresjonsenhet som gjør den enda enklere å bruke og installere. Tetningsmodulene kan tilpasses kabler og rør i ulike størrelser og kan velges ut fra spesifikke krav til IP- eller UL/NEMA-klassifisering.



- Arealeffektiv
- Rask og enkel å installere
- Godkjent for kabelavslutning

Produktegenskaper



IP/UL NEMA

Struktur for installasjon



Kabinetter
og
kapslinger



Metall

Festetype



Bolting

Graderinger og sertifikater

Tetthet

- IP 66/67 i henhold til IEC 60529, UL/NEMA 4,4X,12,13

Rammedimensjoner

mm/kg

Rammevariantene nedenfor er et begrenset utvalg. Du kan besøke [roxtec.com](https://www.roxtec.com) for det komplette utvalget av rammer og konfigurasjoner.


Tittel	Rammeåpninger	Fyllplass	Utvendige mål WxHxD	Utsparingsmål w x h	Vekt	Art.nr.
CSP 32 AISI316 FRAME ASSEMBLY	4	40 x 80	223 x 140 x 63.5	201 x 109	2.9	233729
CSP 16 AISI316 FRAME ASSEMBLY	2	40 x 80	131 x 140 x 63.5	109(+1/-0.5) x 109(+1/-0.5)	1.8	233728

Tetningskomponentdata


Tetningskomponenter



smøremiddel



HD-modul med Multidiameter™



HD solide kompensasjonsmodul

For ytterligere informasjon, kan du besøke www.roxtec.com.

Forhåndskonfigurerte gjennomføringskit

mm/kg















CSP 32/8

CSP 16/4

CSP 16/16

CSP 32/32

CSP 32/41

CSP 32/20

CSP 16/10

Tittel	Konfigurasjon	Utvendige mål WxHxD	Utsparingsmål w x h	Vekt	Art.nr.
CSP 32/8	8x (9.5-31.5)	223 x 140 x 63.5	201 x 109	3.1	241713
CSP 16/4	4x (9.5-31.5)	131 x 140 x 63.5	109 x 109	1.8	241194
CSP 16/16	16x (3.5-15.5)	131 x 140 x 63.5	109 x 109	2.1	241192
CSP 32/32	32x (3.5-15.5)	223 x 140 x 63.5	201 x 109	3.6	241716
CSP 32/41	1x (9.5-31.5), 16x (3.5-15.5), 24x (3.5-9.5)	223 x 140 x 63.5	201 x 109	3.1	241718
CSP 32/20	4x (9.5-31.5), 16x (3.5-15.5)	223 x 140 x 63.5	201 x 109	3.7	241717
CSP 16/10	2x (9.5-31.5), 8x (3.5-15.5)	131 x 140 x 63.5	109 x 109	2.1	241193

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2025-12-12