



Passaggio Roxtec ComSeal BG™

Sistemi di sigillatura conformi allo standard IP 55 per il collegamento e la messa a terra.

Roxtec ComSeal BG™ è classificato per IP 55 e progettato per collegamento e messa a terra di cavi e tubi blindati o armati. Il sistema di sigillatura è disponibile con telaio in alluminio nichelato e in una dimensione unica per ospitare fino a 32 cavi. I moduli di sigillatura Roxtec BG™ sono adattabili a cavi e tubi di dimensioni differenti e possono anche garantire capacità di riserva integrata.



- Previene l'ingresso di roditori
- Leggero
- Compatto
- Consente la sigillatura di cavi precablati
- Consente capacità di riserva integrata
- Adatto a cavi e tubi di misure diverse

Caratteristiche



IP/UL NEMA



Sicurezza elettrica

Struttura dell'installazione



Armadi e quadri

Tipo di montaggio



Imbullonatura

Ratings e certificati

Tenuta

- IP 55 in accordo a IEC 60529, UL/NEMA 3,12,12K

Supporti

- Messa a terra integrata

Dimensioni telaio

mm/kg

Le varianti di telaio seguenti rappresentano una selezione limitata. Per la gamma completa di telai e configurazioni, visita [roxtec.com](https://www.roxtec.com).


Titolo	Aperture del telaio	Spazio di riempimento	Dimensioni esterne WxHxD	Dimensioni apertura w x h	Peso	Art. Nr.
COMSEAL 32 BG FRAME ASSEMBLY	2	40 x 160	135 x 241 x 56	103(+1/-1) x 209(+1/-1)	1	159708

Dati relativi ai componenti

Componenti per la sigillatura



Lubrificante




Moduli CM BG™ con Multidiameter™

Per informazioni dettagliate, visita la pagina [roxtec.com](https://www.roxtec.com).



Kit pre-configurati


mm/kg



COMSEAL 32/20 BG



COMSEAL 32/8 BG



COMSEAL 32/32 BG

Titolo	Configurazione	Dimensioni esterne WxHxD	Dimensioni apertura w x h	Peso	Art. Nr.
COMSEAL 32/20 BG	16x (3.5-16.5), 4x (9.5-32.5)	135 x 241 x 56	103(+1/-1) x 209(+1/-1)	1.8	196984
COMSEAL 32/8 BG	8x (9.5-32.5)	135 x 241 x 56	103(+1/-1) x 209(+1/-1)	1.8	196985
COMSEAL 32/32 BG	32x (3.5-16.5)	135 x 241 x 56	103(+1/-1) x 209(+1/-1)	1.8	196987

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2025-03-12