



# Roxtec ComSeal BG™

본딩과 접지를 위한 IP 55 등급

Roxtec ComSeal BG™는 외장 및 금속 피복 케이블과 파이프의 본딩과 접지에 대해 IP 55 등급을 받았습니다. 씰은 니켈 도금 알루미늄 프레임이 있는 한 가지 크기로 제공되며, 최대 32개의 케이블을 수용할 수 있습니다. Roxtec BG™ 씰링 모듈은 다양한 규격의 케이블과 파이프에 적용 가능하며 스페어 공간을 만들 수도 있습니다.



- 설치류 차단
- 경량
- 공간 효율성
- 종단 케이블 허용
- 예비 공간 포함 제공
- 다양한 사이즈의 케이블 및 파이프에 적용

#### 제품 특장점





IP/UL NEMA

전기관련

설치 구조



캐비닌 및 인클로저

장착 유형



볼트체결

## 등급 및 인증

강도

O IEC 60529에 따른 IP 55, UL/NEMA 3,12,12K

지원

O Bonding과 Grounding

## 프레임 치수

#### mm/kg

아래의 프레임 변화는 제한된 선택입니다. 프레임 및 구성의 전체 범위를 보려면 roxtec.com을 방문하십시오.

프레임 입구 모듈설치공간 외부 치수 Art. 번호 COMSEAL 32 BG FRAME 40 x 160 135 x 241 x 56 103(+1/-1) x 209(+1/-1) 159708 ASSEMBLY

## 씰링 컴포넌트 데이터

#### 씰링 컴포넌트





윤활제

CM BG™ 모듈( Multidiame

자세한 내용은 roxtec.com을 방문하십시오.

2025-03-12









## 키트 구성의 관통장비

### mm/kg







COMSEAL 32/20 BG

COMSEAL 32/8 BG

COMSEAL 32/32 BG

구성	구성	<b>외부 치수</b> WxHxD	<b>홀 치수</b> w x h	무게	Art. 번호
COMSEAL 32/20 BG	16x (3.5-16.5), 4x (9.5-32.5)	135 x 241 x 56	103(+1/-1) x 209(+1/-1)	1.8	196984
COMSEAL 32/8 BG	8x (9.5-32.5)	135 x 241 x 56	103(+1/-1) x 209(+1/-1)	1.8	196985
COMSEAL 32/32 BG	32x (3.5-16.5)	135 x 241 x 56	103(+1/-1) × 209(+1/-1)	1.8	196987

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from https://www.roxtec.org/ne/fabrus/syste/fabrus/

https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/
We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2025-03-12

2/2 2025-03-12