



# Roxtec CF 16 BG™ transit

Kabelgennemføring til potentialudligning og jording med lavprofilramme.

Roxtec CF 16 BG™ er en lavprofil tætning af kabelgennemføringer, som er designet til potentialudligning og jording af armerede og metalbeklædte kabler. Gennemføringen er tilgængelig med en ramme i 304 rustfrit stål. Roxtec BG™ tætningsmodulerne kan tilpasses kabler af forskellig størrelse.



- Gnaverbestandig
- Korrosionsbestandig
- Pladsbesparende
- Kan bruges til preterminerede kabler
- Kan tilpasses til kabler og rør af forskellig størrelse

## Produktgenskaber



IP/UL NEMA



Elektrisk sikkerhed

## Byggekonstruktion



El-skabe og kabinetter

## Monteringstype



Bolting

## Normeringer og certifikater

### Tæthed

- IP 66/67 i henhold til IEC 60529

### Understøtter

- Stel og jording

## Rammedimensioner


mm/kg

De nedenstående rammevarianter udgør et begrænset udvalg. Du kan se hele udvalget af rammer og konfigurationer på [roxtec.com](https://www.roxtec.com).

Title	Rammeåbninger	Pakkeareaö	Udvendige mål WxHxD	Åbningsmål w x h	Vægt	Art.-nr.
CF 16 BG AISI304	1	40 x 160	93 x 234 x 42	71(+1/-1) x 187(+2/-0.5)	1.4	216667

## Data om tætningskomponenter


### Tætningskomponenter



CM BG™ fast kompensationsmodul



Lubrikant



CM BG™-moduler med Multidiameter™

For mer information, besøg venligst [roxtec.com](https://www.roxtec.com).



## Foreslåede tætningskit

mm/kg



CF 16/4 BG AISI304

CF 16/10 BG AISI304

CF 16/16 BG AISI304

Title	Konfiguration	Udvendige mål WxHxD	Åbningsmål w x h	Vægt	Art.-nr.
CF 16/4 BG AISI304	4x (9.5-32.5)	93 x 234 x 42	71(+1/-1) x 187(+2/-0.5)	1.4	216685
CF 16/10 BG AISI304	8x (3.5-16.5), 2x (9.5-32.5)	93 x 234 x 42	71(+1/-1) x 187(+2/-0.5)	1.4	216687
CF 16/16 BG AISI304	16x (3.5-16.5)	93 x 234 x 42	71(+1/-1) x 187(+2/-0.5)	1.4	216686

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2025-03-15