



# Roxtec CF 16 BG™ - läpivienti

Matalaprofiilisella kehyksellä varustettu kaapeliläpivienti potentiaalintasaukseen ja maadoitukseen.

Roxtec CF 16 BG™ on matalaprofiilinen kaapeliläpivientitiiviste armeerattujen tai metalliverhoiltujen kaapelien potentiaalintasaukseen ja maadoitukseen. Läpivienti on saatavana ruostumattomasta 304-teräksestä valmistetulla kehyksellä. Roxtec BG™ -tiivistysmoduulit sopivat erikokoisiin kaapeleihin.



- Jyrsijäsuojattu
- Korroosiosuojattu
- Tilatehokas
- Sopii kaapeleille joissa on liitin
- Sopii erikokoisiin kaapeleihin ja putkiin

## Tuotteen ominaisuudet



IP/UL NEMA



Sähtöturvallisuus

## Asennusrakenne



Kaapit ja kotelot

## Asennustyyppi



Pulttaus

## Luokitukset ja sertifiointit

### Tiiviys

- IP 66/67 standardin IEC 60529 mukaan

### Tuki

- Potentiaalintasaus ja maadoitus

## Kehyksen mitat


mm/kg

Alla olevat kehysvaihtoehdot ovat vain osa valikoimastamme. Kattava valikoima kehyksiä ja kokoonpanoja löytyy osoitteesta [roxtec.com](https://www.roxtec.com).

Otsikko	Kehysaukot	Pakkaustila	Ulkomitat WxHxD	Aukon mitat w x h	Paino	Tuotenro
CF 16 BG AISI304	1	40 x 160	93 x 234 x 42	71(+1/-1) x 187(+2/-0.5)	1.4	216667

## Tiivistyskomponenttien tiedot


### Tiivistyskomponentit



CM BG™ -umpimoduuli



Roxtec-asennusrasva



CM BG™ Multidiameter™ -moduulit

Lisätietoja on osoitteessa [roxtec.com](https://www.roxtec.com).



## Valmiiksi määritetyt läpivientisarjat


mm/kg



CF 16/4 BG AISI304



CF 16/10 BG AISI304



CF 16/16 BG AISI304

Otsikko	Kokoonpano	Ulkomitat WxHxD	Aukon mitat w x h	Paino	Tuotenro
CF 16/4 BG AISI304	4x (9.5-32.5)	93 x 234 x 42	71(+1/-1) x 187(+2/-0.5)	1.4	216685
CF 16/10 BG AISI304	8x (3.5-16.5), 2x (9.5-32.5)	93 x 234 x 42	71(+1/-1) x 187(+2/-0.5)	1.4	216687
CF 16/16 BG AISI304	16x (3.5-16.5)	93 x 234 x 42	71(+1/-1) x 187(+2/-0.5)	1.4	216686

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2025-03-15