



Brtneni prsten Roxtec CF 16 BG™

Prolaz kabela za spajanje i uzemljenje s okvirom niskog profila.

Roxtec CF 16 BG™ niskoprofilni je brtneni okvir namijenjen za izjednačavanje vezivanja i uzemljenje armiranih i metalom prevučeni kabela. Brtneni prsten dostupan je s okvirom od nehrđajućeg čelika 304. Brtneni moduli Roxtec BG™ mogu se prilagoditi kabelima različitih veličina.



- Štiti od glodavaca
- Otpornost na koroziju
- Površinski učinkovito
- Dopušta pred-terminirane kabele
- Prilagođava se kabelima i cijevima različitih veličina

Karakteristike proizvoda



IP/UL NEMA



Električna sigurnost

Struktura instalacije



Ormari i kućišta

Vrsta montaže



Pričvršćivanje vijcima

Klase i certifikati

Nepropusnost

- IP 66/67 prema IEC 60529

Podržava

- Povezivanje i uzemljenje

Dimenzije okvira


mm/kg

Varijante okvira u nastavku ograničen su izbor. Za cijeli raspon okvira i konfiguracija posjetite [roxtec.com](https://www.roxtec.com).

Proizvod	Otvori okvira	Prostor za smještaj	Vanjske dimenzije WxHxD	Dimenzije otvora w x h	Težina	Broj artikla
CF 16 BG AISI304	1	40 x 160	93 x 234 x 42	71(+1/-1) x 187(+2/-0.5)	1.4	216667

Komponente za brtvljenje


Komponente za brtvljenje



Čvrsti kompenzacijski modul CM BG™



Mazivo Roxtec



Modul CM BG™ sa značajkom Multidiameter™

Za detaljne informacije posjetite [roxtec.com](https://www.roxtec.com).



Unaprijed konfigurirani kompleti za prolaze

mm/kg



CF 16/4 BG AISI304

CF 16/10 BG AISI304

CF 16/16 BG AISI304

Proizvod	Konfiguracija	Vanjske dimenzije WxHxD	Dimenzije otvora w x h	Težina	Broj artikla
CF 16/4 BG AISI304	4x (9.5-32.5)	93 x 234 x 42	71(+1/-1) x 187(+2/-0.5)	1.4	216685
CF 16/10 BG AISI304	8x (3.5-16.5), 2x (9.5-32.5)	93 x 234 x 42	71(+1/-1) x 187(+2/-0.5)	1.4	216687
CF 16/16 BG AISI304	16x (3.5-16.5)	93 x 234 x 42	71(+1/-1) x 187(+2/-0.5)	1.4	216686

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on = 2025-03-15