



Passaggio Roxtec CF 16 BG™

Passaggio cavi per collegamento e messa a terra con telaio a basso profilo.

Roxtec CF 16 BG™ è un sistema di sigillatura con telaio di dimensioni ridotte progettato per collegamento e messa a terra di cavi e tubi blindati o armati. Il passaggio è disponibile con telaio in acciaio inox 304. I moduli di sigillatura Roxtec BG™ sono adattabili a cavi di diverse dimensioni.



- Previene l'ingresso di roditori
- Resistente alla corrosione
- Compatto
- Consente la sigillatura di cavi precablati
- Adatto a cavi e tubi di misure diverse

Caratteristiche



IP/UL NEMA



Sicurezza elettrica

Struttura dell'installazione



Armadi e quadri

Tipo di montaggio



Imbullonatura

Ratings e certificati

Tenuta

- IP 66/67 in accordo a IEC 60529

Supporti

- Messa a terra integrata

Dimensioni telaio


mm/kg

Le varianti di telaio seguenti rappresentano una selezione limitata. Per la gamma completa di telai e configurazioni, visita [roxtec.com](https://www.roxtec.com).

Titolo	Aperture del telaio	Spazio di riempimento	Dimensioni esterne WxHxD	Dimensioni apertura w x h	Peso	Art. Nr.
CF 16 BG AISI304	1	40 x 160	93 x 234 x 42	71(+1/-1) x 187(+2/-0.5)	1.4	216667

Dati relativi ai componenti


Componenti per la sigillatura



Modulo di compensazione CM BG™



Lubrificante



Moduli CM BG™ con Multidiameter™

Per informazioni dettagliate, visita la pagina [roxtec.com](https://www.roxtec.com).



Kit pre-configurati

mm/kg



CF 16/4 BG AISI304



CF 16/10 BG AISI304



CF 16/16 BG AISI304

Titolo	Configurazione	Dimensioni esterne WxHxD	Dimensioni apertura w x h	Peso	Art. Nr.
CF 16/4 BG AISI304	4x (9.5-32.5)	93 x 234 x 42	71(+1/-1) x 187(+2/-0.5)	1.4	216685
CF 16/10 BG AISI304	8x (3.5-16.5), 2x (9.5-32.5)	93 x 234 x 42	71(+1/-1) x 187(+2/-0.5)	1.4	216687
CF 16/16 BG AISI304	16x (3.5-16.5)	93 x 234 x 42	71(+1/-1) x 187(+2/-0.5)	1.4	216686

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2025-03-15