



Roxtec CF 16 BG™ geçiş

Metal çerçeve ile topraklama için kablo geçişi.

Roxtec CF 16 BG™ zırlı ve metal kaplı kabloların topraklanması için tasarlanmış bir kablo girişi yalıtım malzemesidir. Geçişte, 304 paslanmaz çerçeve mevcuttur. Roxtec BG™ yalıtım modülleri farklı ölçülerde kabloları uyarlabilir.



- Kemirgenelere dayanıklı
- Paslanmaya dayanıklı
- Yüzeyi verimli kullanır
- Sonlandırılmış kabloları izin verir
- Farklı ölçülerde kablo ve borulara uyarlabilir

Ürün özellikleri



IP/UL NEMA



Elektrik güvenliği

Montaj yapılacak yapı



Panolar ve muhafazalar

Montaj tipi



Cıvatalama

Derecelendirmeler ve sertifikalar

Sızdırmazlık

- IEC 60529'a göre IP 66/67

Destekler

- Topraklama

Çerçeve boyutları


mm/kg

Aşağıdaki çerçeve çeşitleri sınırlı sayıda seçenektir. Çerçeve ve yapılandırma yelpazesinin tamamı için [roxtec.com](https://www.roxtec.com) adresini ziyaret edin.

Başlık	Çerçeve açıklıkları	Modül koyulan alan	Dış boyutlar WxHxD	Açıklık boyutları w x h	Ağırlık	Madde Numarası
CF 16 BG AISI304	1	40 x 160	93 x 234 x 42	71(+1/-1) x 187(+2/-0.5)	1.4	216667

Yalıtım elemanı verileri


Yalıtım elemanları



CM BG™ kör modülü



Kayganlaştırıcı



MultiDiameter™ özellikli CM BG™ modülleri

Ayrıntılı bilgi için lütfen [roxtec.com](https://www.roxtec.com) adresini ziyaret edin.



Önceden yapılandırılmış geçiş kitleri

mm/kg



Başlık	Konfigürasyon	Dış boyutlar WxHxD	Açıklık boyutları w x h	Ağırlık	Madde Numarası
CF 16/4 BG AISI304	4x (9.5-32.5)	93 x 234 x 42	71(+1/-1) x 187(+2/-0.5)	1.4	216685
CF 16/10 BG AISI304	8x (3.5-16.5), 2x (9.5-32.5)	93 x 234 x 42	71(+1/-1) x 187(+2/-0.5)	1.4	216687
CF 16/16 BG AISI304	16x (3.5-16.5)	93 x 234 x 42	71(+1/-1) x 187(+2/-0.5)	1.4	216686

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2025-03-15