



Prostupy Roxtec CSP BG

Těsnění skříně pro aplikace spojení a uzemnění.

Roxtec CSP 16/32 je zařízení pro vícekabelové a potrubní průchody pro skříně a rozvaděče. Rámeček je vyroben z nerezové oceli AISI316 a je dostupný ve variantách pro až 16 nebo 32 kabelů. Je vybaven integrovanou kompresní jednotkou, která dále usnadňuje použití a instalaci. Těsnicí moduly lze upravit pro různé velikosti kabelů a potrubí a lze je vybírat podle konkrétních požadavků na stupeň krytí IP nebo UL/NEMA a pro spojení a uzemnění.



- Kompaktní
- Rychlá a snadná instalace
- Umožňuje použití kabelů s koncovkami

Vlastnosti výrobku



IP/UL NEMA



Elektrická bezpečnost

Struktura instalace



Skříně a rozvaděče



Kov

Typ montáže



Příšroubování

Specifikace a certifikáty

Těsnost

- IP 66/67 podle IEC 60529, UL/NEMA 4,4X,12,13

Podporuje

- Pospojování a uzemnění

Rozměry rámu

mm/kg

Níže uvedené verze rámu jsou pouze některé možnosti. Úplnou nabídku rámu a konfigurací najdete na stránkách [roxtec.com](https://www.roxtec.com).


Název	Otvory rámu	Prostor utěsnění	Vnější rozměry WxHxD	Rozměry otvoru w x h	Hmotnost Typ. č.
CSP 32 AISI316 FRAME ASSEMBLY	4	40 x 80	223 x 140 x 63.5	201 x 109	2.9 233729
CSP 16 AISI316 FRAME ASSEMBLY	2	40 x 80	131 x 140 x 63.5	109(+1/-0.5) x 109(+1/-0.5)	1.8 233728

Údaje o izolačních komponentách


Těsnící komponenty



Mazivo Roxtec



Plný kompenzační modul CM BG™



Moduly CM BG™ s technologií Multidiameter™

Podrobné informace najdete na stránkách www.roxtec.com.



Konfigurované soupravy průstupů

mm/kg



CSP 16/16 BG



CSP 32/8 BG



CSP 32/20 BG



CSP 16/10 BG



CSP 32/32 BG



CSP 16/4 BG

Název	Konfigurace	Vnější rozměry WxHxD	Rozměry otvoru w x h	Hmotnost Typ. č.	
CSP 16/16 BG	16x (3.5-16.5)	131 x 140 x 63.5	109 x 109	2.2	241723
CSP 32/8 BG	8x (9.5-32.5)	223 x 140 x 63.5	201 x 109	3.1	241724
CSP 32/20 BG	4x (9.5-32.5), 16x (3.5-16.5)	223 x 140 x 63.5	201 x 109	3.7	241725
CSP 16/10 BG	2x (9.5-32.5), 8x (3.5-16.5)	131 x 140 x 63.5	109 x 109	2.2	241722
CSP 32/32 BG	32x (3.5-16.5)	223 x 140 x 63.5	201 x 109	3.7	243522
CSP 16/4 BG	4x (9.5-32.5)	131 x 140 x 63.5	109 x 109	1.8	241720

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2025-12-13



Roxtec ® and Multidiameter ®
are registered trademarks of Roxtec
in Sweden and/or other countries.