



Roxtec CSP BG-gennemføringer

Kabinetforsegling til potentialudlignings- og jordingsapplikationer.

Roxtec CSP 16/32 er en multi-kabel- og rørgennemføring til skabe og kabinetter. Rammen er fremstillet af AISI316 rustfrit stål og fås i størrelser op til 16 eller 32 kabler. Den har en integreret komprimeringsenhed til yderligere at forbedre bruger- og installationsvenlighed. Tætningsmodulerne kan tilpasses til kabler og rør i forskellige størrelser og kan vælges i overensstemmelse med specifikke behov for IP- eller UL/NEMA-klassificeringer samt potentialudligning og jording.



- Pladsbesparende
- Hurtig og nem at montere
- Kan bruges til preterminerede kabler

Produktegenskaber



IP/UL NEMA



Elektrisk sikkerhed

Byggekonstruktion



El-skabe og kabinetter



Metal

Monteringstype



Boltning

Normeringer og certifikater

Tæthed

- IP 66/67 i henhold til IEC 60529, UL/NEMA 4,4X,12,13

Understøtter

- Stel og jording

Rammedimensioner

mm/kg

De nedenstående rammevarianter udgør et begrænset udvalg. Du kan se hele udvalget af rammer og konfigurationer på [roxtec.com](https://www.roxtec.com).


Title	Rammeåbninger	Pakkeareaö	Udvendige mål WxHxD	Åbningsmål w x h	Vægt	Art.-nr.
CSP 32 AISI316 FRAME ASSEMBLY	4	40 x 80	223 x 140 x 63.5	201 x 109	2.9	233729
CSP 16 AISI316 FRAME ASSEMBLY	2	40 x 80	131 x 140 x 63.5	109(+1/-0.5) x 109(+1/-0.5)	1.8	233728

Data om tætningskomponenter


Tætningskomponenter



Lubrikant



CM BG™ fast kompensationsmodul



CM BG™-moduler med Multidiameter™

For mer information, besøg venligst [roxtec.com](https://www.roxtec.com).

Foreslåede tætningskit

mm/kg

					
CSP 16/16 BG	CSP 32/8 BG	CSP 32/20 BG	CSP 16/10 BG	CSP 32/32 BG	CSP 16/4 BG
Title	Konfiguration	Udvendige mål WxHxD	Åbningsmål w x h	Vægt	Art.-nr.
CSP 16/16 BG	16x (3.5-16.5)	131 x 140 x 63.5	109 x 109	2.2	241723
CSP 32/8 BG	8x (9.5-32.5)	223 x 140 x 63.5	201 x 109	3.1	241724
CSP 32/20 BG	4x (9.5-32.5), 16x (3.5-16.5)	223 x 140 x 63.5	201 x 109	3.7	241725
CSP 16/10 BG	2x (9.5-32.5), 8x (3.5-16.5)	131 x 140 x 63.5	109 x 109	2.2	241722
CSP 32/32 BG	32x (3.5-16.5)	223 x 140 x 63.5	201 x 109	3.7	243522
CSP 16/4 BG	4x (9.5-32.5)	131 x 140 x 63.5	109 x 109	1.8	241720

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2025-12-13