



Roxtec CSP BG-genomföringar

Skåpstätning för potentialutjämning och skyddsjordning.

Roxtec CSP 16/32 är en multikabel- och rör genomföring för skåp och kapslingar. Ramen är tillverkad av AISI316 rostfritt stål och finns i storlekar för upp till 16 eller 32 kablar. Den har en integrerad kompressionsenhet för att ytterligare förbättra användbarheten och underlätta installationen. Tätningsmodulerna är anpassningsbara till kablar och rör i olika storlekar och kan väljas utifrån specifika behov av IP- eller UL/NEMA-klassificeringar samt för potentialutjämning och skyddsjordning.



- Utrymmeseffektiv
- Snabb och enkel installation
- Möjliggör användning av förterminerade kablar

Produktegenskaper



IP/UL NEMA



Elsäkerhet

Konstruktion för installation



Skåp & kapslingar



Metall

Monteringssätt



Bultning

Klassningar & certifikat

Täthet

- IP 66/67 enligt IEC 60529, UL/NEMA 4,4X,12,13

Stödjer

- Potentialutjämning och skyddsjordning

Ramdimensioner

mm/kg

Ramvarianterna nedan är ett begränsat urval. Du hittar hela utbudet av ramar och konfigurationer på [roxtec.com](https://www.roxtec.com).


Titel	Ramöppningar	Packningsutrymme	Ytermått WxHxD	Öppningens mått w x h	Vikt	Art. nr
CSP 32 AISI316 FRAME ASSEMBLY	4	40 x 80	223 x 140 x 63.5	201 x 109	2.9	233729
CSP 16 AISI316 FRAME ASSEMBLY	2	40 x 80	131 x 140 x 63.5	109(+1/-0.5) x 109(+1/-0.5)	1.8	233728

Information om tätningskomponenter


Tätningskomponenter



smörjmedel



CM BG™ solid kompensationsmodul



CM BG™-moduler med Multidiameter™

Detaljerad information finns på [roxtec.com](https://www.roxtec.com).

Förkonfigurerade genomföringskit

mm/kg

					
CSP 16/16 BG	CSP 32/8 BG	CSP 32/20 BG	CSP 16/10 BG	CSP 32/32 BG	CSP 16/4 BG
Titel	Konfigurering	Ytermått WxHxD	Öppningens mått w x h	Vikt	Art. nr
CSP 16/16 BG	16x (3.5-16.5)	131 x 140 x 63.5	109 x 109	2.2	241723
CSP 32/8 BG	8x (9.5-32.5)	223 x 140 x 63.5	201 x 109	3.1	241724
CSP 32/20 BG	4x (9.5-32.5), 16x (3.5-16.5)	223 x 140 x 63.5	201 x 109	3.7	241725
CSP 16/10 BG	2x (9.5-32.5), 8x (3.5-16.5)	131 x 140 x 63.5	109 x 109	2.2	241722
CSP 32/32 BG	32x (3.5-16.5)	223 x 140 x 63.5	201 x 109	3.7	243522
CSP 16/4 BG	4x (9.5-32.5)	131 x 140 x 63.5	109 x 109	1.8	241720

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2025-12-13