



Roxtec CSP BG 穿隔系统

适用于接地的箱柜密封

Roxtec CSP 16/32 是用于机柜和箱柜的多电缆和管道穿隔装置。 该框架采用 AISI316 不锈 钢制造チ并提供可容纳至多 16 根或 32 根电缆的尺寸规格可选。 它带有集成的压紧 装置チ可进一步提升使用便利性和安装效率。 密封模块可适配不同型号的电缆 和管道チ并可根据 IP 或 UL/NEMA 等级及接地应用的特定需求进行选择。



- 节省空间
- 安装快速便捷
- 允许使用预端接电缆

产品特性





IP/UL NEMA

~ 12

安装结构





安装类型



等级和证书

密封性

● 符合 IEC 60529 标准 IP 66/67 防护等级, UL/NEMA 4,4X,12,13

支持



框架尺寸

mm/kg

下方的不同框架只是部分选择。 要了解全部的框架和配置チ请访问 roxtec.com。

| 标题 | 框架开口 | 密封空间 | 外部尺寸 WxHxD | 开孔尺寸 w x h | 重量 | 产品编号 |
|----------------------------------|------|---------|----------------------|-----------------------------|-----|--------|
| CSP 32 AISI316 FRAME ASSEMBLY | 4 | 40 x 80 | 223 x 140 x 63.5 | 201 x 109 | 2.9 | 233729 |
| CSP 16 AISI316 FRAME ASSEMBLY | 2 | 40 x 80 | 131 x 140 x 63.5 | 109(+1/-0.5) x 109(+1/-0.5) | 1.8 | 233728 |

密封组件数据

密封组件







CM BG™ 盲堵模块

Multidiameter™ソ多径ゾCM BG™ 模块

润滑脂 如需了解详细信息チ请访问 roxtec.com。

1/2 2025-12-13



https://www.roxtec.com/linktransit/zh-cn/solution/54604



预装配的穿隔套件

mm/kg













CSP 16/16 BG CSP 32/8 BG

CSP 32/20 BG

CSP 16/10 BG

CSP 32/32 BG

CSP 16/4 BG

| 标题 | 配置 | 外部尺寸 WxHxD | 开孔尺寸 w x h | 重量 | 产品编号 |
|--------------|-------------------------------|------------------|---------------|-----|--------|
| CSP 16/16 BG | 16x (3.5-16.5) | 131 x 140 x 63.5 | 109 x 109 | 2.2 | 241723 |
| CSP 32/8 BG | 8x (9.5-32.5) | 223 x 140 x 63.5 | 201 x 109 | 3.1 | 241724 |
| CSP 32/20 BG | 4x (9.5-32.5), 16x (3.5-16.5) | 223 x 140 x 63.5 | 201 x 109 | 3.7 | 241725 |
| CSP 16/10 BG | 2x (9.5-32.5), 8x (3.5-16.5) | 131 x 140 x 63.5 | 109 x 109 | 2.2 | 241722 |
| CSP 32/32 BG | 32x (3.5-16.5) | 223 x 140 x 63.5 | 201 x 109 | 3.7 | 243522 |
| CSP 16/4 BG | 4x (9.5-32.5) | 131 x 140 x 63.5 | 109 x 109 | 1.8 | 241720 |

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2025-12-13

2025-12-13