




Prostup Roxtec GOH FL100

Otevíratelný prostup pro stávající kabely, včetně široké příruby vhodný pro přišroubování k betonovým konstrukcím.

Roxtec GOH FL100 je otevíratelné těsnění pro kabely a potrubí, které umožňuje instalaci kolem již vedených rozvodů. Obdélníkový ocelový rám má 100 mm širokou přírubu s otvory pro šrouby v blízkosti vnějšího obvodu, aby bylo zajištěno správné upevnění a zabránilo se riziku prasklin. Prostup je správnou volbou při šroubování do betonu.

- Optimální pro dodatečnou montáž
- Otevíratelný



Vlastnosti výrobku



Protipožární



IP/UL NEMA

Struktura instalace



Beton



Cihla

Typ montáže



Přišroubování

Specifikace a certifikáty

Protipožární ochrana

- Požární odolnost E/EI podle EN 13501

Těsnost

- IP 68

Rozměry rámu

mm/kg

Níže uvedené verze rámu jsou pouze některé možnosti. Úplnou nabídku rámu a konfigurací najdete na stránkách [roxtec.com](https://www.roxtec.com).


Název	Otvory rámu	Prostor utěsnění	Vnější rozměry WxHxD	Rozměry otvoru w x h	Hmotnost Typ. č.
GOH 2x1 FL100 AISI316	1	120 x 60	332.5 x 313 x 60	148(+5/-5) x 128(+5/-5)	7 214791
GOH 6x2 FL100 AISI316	2	120 x 180	465 x 430 x 60	280(+5/-5) x 245(+5/-5)	12 164359
GOH 6x3 FL100 AISI316	3	120 x 180	597.5 x 430 x 60	413(+5/-5) x 245(+5/-5)	14.4 157824
GOH 6x4 FL100 AISI316	4	120 x 180	730 x 430 x 60	545(+5/-5) x 245(+5/-5)	18.7 125356
GOH 8x1 FL100 AISI316	1	120 x 240	332.5 x 490 x 60	148(+5/-5) x 305(+5/-5)	10 179208
GOH 8x2 FL100 AISI316	2	120 x 240	465 x 490 x 60	280(+5/-5) x 305(+5/-5)	13.4 110472
GOH 8x3 FL100 AISI316	3	120 x 240	597.5 x 490 x 60	413(+5/-5) x 305(+5/-5)	16 104111
GOH 8x4 FL100 AISI316	4	120 x 240	730 x 490 x 60	545(+5/-5) x 305(+5/-5)	19.4 173441
GOH 2x1 FL100 GALV	1	120 x 60	332.5 x 313 x 60	148(+5/-5) x 128(+5/-5)	7 124009
GOH 2x2 FL100 GALV	2	120 x 60	465 x 313 x 60	280(+5/-5) x 128(+5/-5)	9.6 250893
GOH 2x2 FL100 AISI316	2	120 x 60	465 x 313 x 60	280(+5/-5) x 128(+5/-5)	9.6 250896
GOH 2x3 FL100 GALV	3	120 x 60	597.5 x 313 x 60	413(+5/-5) x 128(+5/-5)	12.2 250894
GOH 2x4 FL100 GALV	4	120 x 60	730 x 313 x 60	545(+5/-5) x 128(+5/-5)	15 179978
GOH 4x1 FL100 GALV	1	120 x 120	332.5 x 371.5 x 60	148(+5/-5) x 187(+5/-5)	8.1 107250
GOH 4x2 FL100 GALV	2	120 x 120	465 x 371.5 x 60	280(+5/-5) x 187(+5/-5)	11 121490
GOH 4x3 FL100 GALV	3	120 x 120	597.5 x 371.5 x 60	413(+5/-5) x 187(+5/-5)	13.5 192221
GOH 4x4 FL100 GALV	4	120 x 120	730 x 371.5 x 60	545(+5/-5) x 187(+5/-5)	18 121489
GOH 6x1 FL100 GALV	1	120 x 180	332.5 x 430 x 60	148(+5/-5) x 245(+5/-5)	7.4 179403
GOH 6x2 FL100 GALV	2	120 x 180	465 x 430 x 60	280(+5/-5) x 245(+5/-5)	12 179416
GOH 6x3 FL100 GALV	3	120 x 180	597.5 x 430 x 60	413(+5/-5) x 245(+5/-5)	15 179976
GOH 6x4 FL100 GALV	4	120 x 180	730 x 430 x 60	545(+5/-5) x 245(+5/-5)	18 119419
GOH 2x3 FL100 AISI316	3	120 x 60	597.5 x 313 x 60	413(+5/-5) x 128(+5/-5)	12.2 250897
GOH 8x1 FL100 GALV	1	120 x 240	332.5 x 490 x 60	148(+5/-5) x 305(+5/-5)	9 151629



Název	Otvory rámu	Prostor utěsnění	Vnější rozměry WxHxD	Rozměry otvoru w x h	Hmotnost Typ. č.
GOH 8x2 FL100 GALV	2	120 x 240	465 x 490 x 60	280(+5/-5) x 305(+5/-5)	13 150141
GOH 8x3 FL100 GALV	3	120 x 240	597.5 x 490 x 60	413(+5/-5) x 305(+5/-5)	17 155328
GOH 8x4 FL100 GALV	4	120 x 240	730 x 490 x 60	545(+5/-5) x 305(+5/-5)	20.3 121488
GOH 2x4 FL100 AISI316	4	120 x 60	730 x 313 x 60	545(+5/-5) x 128(+5/-5)	14.9 250898
GOH 4x1 FL100 AISI316	1	120 x 120	332.5 x 371.5 x 60	148(+5/-5) x 187(+5/-5)	7.6 152890
GOH 4x2 FL100 AISI316	2	120 x 120	465 x 371.5 x 60	280(+5/-5) x 187(+5/-5)	10.8 215709
GOH 4x3 FL100 AISI316	3	120 x 120	597.5 x 371.5 x 60	413(+5/-5) x 187(+5/-5)	14 215812
GOH 4x4 FL100 AISI316	4	120 x 120	730 x 371.5 x 60	545(+5/-5) x 187(+5/-5)	16.8 227620
GOH 6x1 FL100 AISI316	1	120 x 180	332.5 x 430 x 60	148(+5/-5) x 245(+5/-5)	8.6 157979

Údaje o izolačních komponentách


Těsnící komponenty



Vymezovací destička
Roxtec




Souprava těsnění Roxtec



Plný kompenzační modul
RM



Klíňové těsnění a souprava
klíňových těsnění Roxtec



Modul RM s technologií
Multidiameter™

Příslušenství



Držáky Roxtec



Předkompresní nástroj
Roxtec



Mazivo Roxtec

Podrobné informace najdete na stránkách www.roxtec.com.

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use. Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended. Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses. The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>. We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright. This document was generated on: 2026-01-13



Roxtec ® and Multidiameter ®
are registered trademarks of Roxtec
in Sweden and/or other countries.