



Roxtec SFOH transit

Openable transit for existing cables, including a flange with pre-drilled holes for bolting to the structure.

The Roxtec SFOH is an openable cable and pipe seal that enables installation around already routed services. The rectangular steel frame has a flange with pre-drilled bolt holes. The transit is the right choice when hot work is unwanted.



- Perfect for retrofit
- Openable

Product characteristics



Fire rated



Watertight



Gas-tight



IP/UL NEMA

Structure of installation



Metal

Mounting type



Bolting

Ratings & certificates

Fire

- A-CLASS according to IMO 2010 FTP Code

Tightness

- Gas: 0.1 bar (catastrophic)
- Water: 1 bar (catastrophic)
- IP 66/67 according to IEC 60529

Frame dimensions

in/lbs

The frame variants below are a limited selection. For the full range of frames and configurations, please visit [roxtec.com](https://www.roxtec.com).

Product	Frame openings	Packing space	External dimensions WxHxD	Aperture dimensions w x h	Weight	Art. no
SFOH 2x1 AISI316	1	4.724 x 2.362	10.256 x 9.488 x 2.362	6.339(+0.197/-0.197) x 5.551(+0.197/-0.197)	15.4	106162
SFOH 6x2 AISI316	2	4.724 x 7.087	15.472 x 14.094 x 2.362	11.535(+0.197/-0.197) x 10.157(+0.197/-0.197)	28.7	118846
SFOH 6x3 AISI316	3	4.724 x 7.087	20.689 x 14.094 x 2.362	16.772(+0.197/-0.197) x 10.157(+0.197/-0.197)	39.7	118847
SFOH 6x4 AISI316	4	4.724 x 7.087	25.906 x 14.094 x 2.362	21.969(+0.197/-0.197) x 10.157(+0.197/-0.197)	45	105325
SFOH 8x1 AISI316	1	4.724 x 9.449	10.256 x 16.457 x 2.362	6.339(+0.197/-0.197) x 12.52(+0.197/-0.197)	35.3	106165
SFOH 8x2 AISI316	2	4.724 x 9.449	15.472 x 16.457 x 2.362	11.535(+0.197/-0.197) x 12.52(+0.197/-0.197)	29.8	106221
SFOH 8x3 AISI316	3	4.724 x 9.449	20.689 x 16.457 x 2.362	16.772(+0.197/-0.197) x 12.52(+0.197/-0.197)	41.4	171369
SFOH 8x4 AISI316	4	4.724 x 9.449	25.906 x 16.457 x 2.362	21.969(+0.197/-0.197) x 12.52(+0.197/-0.197)	49.6	171370
SFOH 2x1 GALV	1	4.724 x 2.362	10.256 x 9.488 x 2.362	6.339(+0.197/-0.197) x 5.551(+0.197/-0.197)	15.4	124472
SFOH 2x2 GALV	2	4.724 x 2.362	15.472 x 9.488 x 2.362	11.535(+0.197/-0.197) x 5.551(+0.197/-0.197)	22	251640
SFOH 2x3 GALV	3	4.724 x 2.362	20.689 x 9.488 x 2.362	16.772(+0.197/-0.197) x 5.551(+0.197/-0.197)	28.9	251641
SFOH 2x2 AISI316	2	4.724 x 2.362	15.472 x 9.488 x 2.362	11.535(+0.197/-0.197) x 5.551(+0.197/-0.197)	22.5	245788
SFOH 2x4 GALV	4	4.724 x 2.362	25.906 x 9.488 x 2.362	21.969(+0.197/-0.197) x 5.551(+0.197/-0.197)	35.7	251642



Product	Frame openings	Packing space	External dimensions WxHxD	Aperture dimensions w x h	Weight	Art. no
SFOH 4x1 GALV	1	4.724 x 4.724	10.256 x 11.791 x 2.362	6.339(+0.197/-0.197) x 7.874(+0.197/-0.197)	18.7	124473
SFOH 4x2 GALV	2	4.724 x 4.724	15.472 x 11.791 x 2.362	11.535(+0.197/-0.197) x 7.874(+0.197/-0.197)	25.4	251643
SFOH 4x3 GALV	3	4.724 x 4.724	20.689 x 11.791 x 2.362	16.772(+0.197/-0.197) x 7.874(+0.197/-0.197)	32.8	251644
SFOH 4x4 GALV	4	4.724 x 4.724	25.906 x 11.791 x 2.362	21.969(+0.197/-0.197) x 7.874(+0.197/-0.197)	41.9	123016
SFOH 6x1 GALV	1	4.724 x 7.087	10.256 x 14.094 x 2.362	6.339(+0.197/-0.197) x 10.157(+0.197/-0.197)	22	175023
SFOH 6x2 GALV	2	4.724 x 7.087	15.472 x 14.094 x 2.362	11.535(+0.197/-0.197) x 10.157(+0.197/-0.197)	29.8	175025
SFOH 6x3 GALV	3	4.724 x 7.087	20.689 x 14.094 x 2.362	16.772(+0.197/-0.197) x 10.157(+0.197/-0.197)	36.6	124470
SFOH 6x4 GALV	4	4.724 x 7.087	25.906 x 14.094 x 2.362	21.969(+0.197/-0.197) x 10.157(+0.197/-0.197)	45	124471
SFOH 8x1 GALV	1	4.724 x 9.449	10.256 x 16.457 x 2.362	6.339(+0.197/-0.197) x 12.52(+0.197/-0.197)	22	175034
SFOH 2x3 AISI316	3	4.724 x 2.362	20.689 x 9.488 x 2.362	16.772(+0.197/-0.197) x 5.551(+0.197/-0.197)	29.5	245789
SFOH 8x2 GALV	2	4.724 x 9.449	15.472 x 16.457 x 2.362	11.535(+0.197/-0.197) x 12.52(+0.197/-0.197)	31.7	254323
SFOH 8x3 GALV	3	4.724 x 9.449	20.689 x 16.457 x 2.362	16.772(+0.197/-0.197) x 12.52(+0.197/-0.197)	40.6	254324
SFOH 8x4 GALV	4	4.724 x 9.449	25.906 x 16.457 x 2.362	21.969(+0.197/-0.197) x 12.52(+0.197/-0.197)	49.6	254325
SFOH 2x4 AISI316	4	4.724 x 2.362	25.906 x 9.488 x 2.362	21.969(+0.197/-0.197) x 5.551(+0.197/-0.197)	36.4	245790
SFOH 4x1 AISI316	1	4.724 x 4.724	10.256 x 11.791 x 2.362	6.339(+0.197/-0.197) x 7.874(+0.197/-0.197)	17.6	106163
SFOH 4x2 AISI316	2	4.724 x 4.724	15.472 x 11.791 x 2.362	11.535(+0.197/-0.197) x 7.874(+0.197/-0.197)	25.8	171353
SFOH 4x3 AISI316	3	4.724 x 4.724	20.689 x 11.791 x 2.362	16.772(+0.197/-0.197) x 7.874(+0.197/-0.197)	32.5	171354
SFOH 4x4 AISI316	4	4.724 x 4.724	25.906 x 11.791 x 2.362	21.969(+0.197/-0.197) x 7.874(+0.197/-0.197)	41	236043
SFOH 6x1 AISI316	1	4.724 x 7.087	10.256 x 14.094 x 2.362	6.339(+0.197/-0.197) x 10.157(+0.197/-0.197)	19.8	106164

Sealing components


Sealing components



Stayplate




sealing kit



RM solid compensation
module



Wedge & Wedge kit



RM module with
Multidiameter™



Holder tools



Pre-compression tools



Lubricant

Accessories

For detailed information, please visit [roxtec.com](https://www.roxtec.com).



The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2026-01-13

