



Passage Roxtec SFOH

Passage ouvrable pour les câbles existants, il est composé d'une bride avec des trous pré-perçés pour le boulonnage à la structure.

Le Roxtec SFOH est un passage de câbles et de tuyaux ouvrable qui permet une installation autour des réseaux déjà acheminés. Le cadre rectangulaire, en acier, est composé d'une bride avec des trous pré-perçés pour les boulons. La traversée est le choix adéquat lorsque les travaux à chaud ne sont pas souhaités.



- Idéal pour la rénovation
- Ouvrable

Caractéristiques du produit



Coupe-feu



Étanche à l'eau



Étanche au gaz



IP/UL NEMA

Structure d'installation



Métal

Type de fixation



Boulonnage

Classements et certificats

Feu

- CLASSE A conformément au code FTP IMO 2010

Étanchéité

- Gaz: 0,1 bars (catastrophique)
- Eau: 1 bars (catastrophique)
- IP 66/67 selon IEC 60529

Dimensions du cadre

mm/kg

Les variantes de cadre ci-dessous sont une sélection limitée. Pour voir la gamme complète de cadres et de configurations, veuillez visiter [roxtec.com](https://www.roxtec.com).

Titre	Ouvertures de cadre	Espace de remplissage	Dimensions externes W x H x D	Dimensions d'ouverture w x h	Poids	N° art.
SFOH 2x1 AISI316	1	120 x 60	260.5 x 241 x 60	161(+5/-5) x 141(+5/-5)	7	106162
SFOH 6x2 AISI316	2	120 x 180	393 x 358 x 60	293(+5/-5) x 258(+5/-5)	13	118846
SFOH 6x3 AISI316	3	120 x 180	525.5 x 358 x 60	426(+5/-5) x 258(+5/-5)	18	118847
SFOH 6x4 AISI316	4	120 x 180	658 x 358 x 60	558(+5/-5) x 258(+5/-5)	20.4	105325
SFOH 8x1 AISI316	1	120 x 240	260.5 x 418 x 60	161(+5/-5) x 318(+5/-5)	16	106165
SFOH 8x2 AISI316	2	120 x 240	393 x 418 x 60	293(+5/-5) x 318(+5/-5)	13.5	106221
SFOH 8x3 AISI316	3	120 x 240	525.5 x 418 x 60	426(+5/-5) x 318(+5/-5)	18.8	171369
SFOH 8x4 AISI316	4	120 x 240	658 x 418 x 60	558(+5/-5) x 318(+5/-5)	22.5	171370
SFOH 2x1 GALV	1	120 x 60	260.5 x 241 x 60	161(+5/-5) x 141(+5/-5)	7	124472
SFOH 2x2 GALV	2	120 x 60	393 x 241 x 60	293(+5/-5) x 141(+5/-5)	10	251640
SFOH 2x3 GALV	3	120 x 60	525.5 x 241 x 60	426(+5/-5) x 141(+5/-5)	13.1	251641
SFOH 2x2 AISI316	2	120 x 60	393 x 241 x 60	293(+5/-5) x 141(+5/-5)	10.2	245788
SFOH 2x4 GALV	4	120 x 60	658 x 241 x 60	558(+5/-5) x 141(+5/-5)	16.2	251642
SFOH 4x1 GALV	1	120 x 120	260.5 x 299.5 x 60	161(+5/-5) x 200(+5/-5)	8.5	124473
SFOH 4x2 GALV	2	120 x 120	393 x 299.5 x 60	293(+5/-5) x 200(+5/-5)	11.5	251643
SFOH 4x3 GALV	3	120 x 120	525.5 x 299.5 x 60	426(+5/-5) x 200(+5/-5)	14.9	251644
SFOH 4x4 GALV	4	120 x 120	658 x 299.5 x 60	558(+5/-5) x 200(+5/-5)	19	123016
SFOH 6x1 GALV	1	120 x 180	260.5 x 358 x 60	161(+5/-5) x 258(+5/-5)	10	175023
SFOH 6x2 GALV	2	120 x 180	393 x 358 x 60	293(+5/-5) x 258(+5/-5)	13.5	175025
SFOH 6x3 GALV	3	120 x 180	525.5 x 358 x 60	426(+5/-5) x 258(+5/-5)	16.6	124470
SFOH 6x4 GALV	4	120 x 180	658 x 358 x 60	558(+5/-5) x 258(+5/-5)	20.4	124471

Titre	Ouvertures de cadre	Espace de remplissage	Dimensions externes WxHxD	Dimensions d'ouverture w x h	Poids	N° art.
SFOH 8x1 GALV	1	120 x 240	260.5 x 418 x 60	161(+5/-5) x 318(+5/-5)	10	175034
SFOH 2x3 AISI316	3	120 x 60	525.5 x 241 x 60	426(+5/-5) x 141(+5/-5)	13.4	245789
SFOH 8x2 GALV	2	120 x 240	393 x 418 x 60	293(+5/-5) x 318(+5/-5)	14.4	254323
SFOH 8x3 GALV	3	120 x 240	525.5 x 418 x 60	426(+5/-5) x 318(+5/-5)	18.4	254324
SFOH 8x4 GALV	4	120 x 240	658 x 418 x 60	558(+5/-5) x 318(+5/-5)	22.5	254325
SFOH 2x4 AISI316	4	120 x 60	658 x 241 x 60	558(+5/-5) x 141(+5/-5)	16.5	245790
SFOH 4x1 AISI316	1	120 x 120	260.5 x 299.5 x 60	161(+5/-5) x 200(+5/-5)	8	106163
SFOH 4x2 AISI316	2	120 x 120	393 x 299.5 x 60	293(+5/-5) x 200(+5/-5)	11.7	171353
SFOH 4x3 AISI316	3	120 x 120	525.5 x 299.5 x 60	426(+5/-5) x 200(+5/-5)	14.8	171354
SFOH 4x4 AISI316	4	120 x 120	658 x 299.5 x 60	558(+5/-5) x 200(+5/-5)	18.6	236043
SFOH 6x1 AISI316	1	120 x 180	260.5 x 358 x 60	161(+5/-5) x 258(+5/-5)	9	106164

Eléments d'étanchéité

Eléments d'étanchéité


Accessoires



Plaque de maintien Roxtec




Kit d'étanchéité Roxtec



Module de compensation plein RM



Wedge et Wedgekit



Module RM avec Multidiameter™



Outils de maintien Roxtec



Outils de pré-compression Roxtec



Lubrifiant Roxtec

Pour plus d'informations, veuillez consulter [roxtec.com](https://www.roxtec.com).

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use. Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended. Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses. The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/> We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright. This document was generated on: 2026-01-13