



Roxtec SFOH-genomföring

Öppningsbar genomföring för befintliga kablar, med en fläns med förborrade hål för skruvfästning i konstruktionen.

Roxtec SFOH är en öppningsbar kabel- och rörgenomföring som möjliggör installation runt redan dragna ledningar. Den rektangulära stålramen har en fläns med förborrade bulthål. Genomföringen är det rätta valet när heta arbeten är oönskade.

- Perfekt för eftermontering
- Öppningsbar



Produktegenskaper



Brandklassad



Vattentät



Gastät



IP/UL NEMA

Konstruktion för installation



Metall

Monteringssätt



Bultning

Klassningar & certifikat

Brand

- A-KLASS enligt IMO 2010 FTP-kod

Täthet

- Gas: 0,1 bar (katastrofmässigt)
- Vatten: 1 bar (katastrofmässigt)
- IP 66/67 enligt IEC 60529

Ramdimensioner

mm/kg

Ramvarianterna nedan är ett begränsat urval. Du hittar hela utbudet av ramar och konfigurationer på [roxtec.com](https://www.roxtec.com).

Titel	Ramöppningar	Packningsutrymme	Yttermått WxHxD	Öppningens mått w x h	Vikt	Art. nr
SFOH 2x1 AISI316	1	120 x 60	260.5 x 241 x 60	161(+5/-5) x 141(+5/-5)	7	106162
SFOH 6x2 AISI316	2	120 x 180	393 x 358 x 60	293(+5/-5) x 258(+5/-5)	13	118846
SFOH 6x3 AISI316	3	120 x 180	525.5 x 358 x 60	426(+5/-5) x 258(+5/-5)	18	118847
SFOH 6x4 AISI316	4	120 x 180	658 x 358 x 60	558(+5/-5) x 258(+5/-5)	20.4	105325
SFOH 8x1 AISI316	1	120 x 240	260.5 x 418 x 60	161(+5/-5) x 318(+5/-5)	16	106165
SFOH 8x2 AISI316	2	120 x 240	393 x 418 x 60	293(+5/-5) x 318(+5/-5)	13.5	106221
SFOH 8x3 AISI316	3	120 x 240	525.5 x 418 x 60	426(+5/-5) x 318(+5/-5)	18.8	171369
SFOH 8x4 AISI316	4	120 x 240	658 x 418 x 60	558(+5/-5) x 318(+5/-5)	22.5	171370
SFOH 2x1 GALV	1	120 x 60	260.5 x 241 x 60	161(+5/-5) x 141(+5/-5)	7	124472
SFOH 2x2 GALV	2	120 x 60	393 x 241 x 60	293(+5/-5) x 141(+5/-5)	10	251640
SFOH 2x3 GALV	3	120 x 60	525.5 x 241 x 60	426(+5/-5) x 141(+5/-5)	13.1	251641
SFOH 2x2 AISI316	2	120 x 60	393 x 241 x 60	293(+5/-5) x 141(+5/-5)	10.2	245788
SFOH 2x4 GALV	4	120 x 60	658 x 241 x 60	558(+5/-5) x 141(+5/-5)	16.2	251642
SFOH 4x1 GALV	1	120 x 120	260.5 x 299.5 x 60	161(+5/-5) x 200(+5/-5)	8.5	124473
SFOH 4x2 GALV	2	120 x 120	393 x 299.5 x 60	293(+5/-5) x 200(+5/-5)	11.5	251643
SFOH 4x3 GALV	3	120 x 120	525.5 x 299.5 x 60	426(+5/-5) x 200(+5/-5)	14.9	251644
SFOH 4x4 GALV	4	120 x 120	658 x 299.5 x 60	558(+5/-5) x 200(+5/-5)	19	123016
SFOH 6x1 GALV	1	120 x 180	260.5 x 358 x 60	161(+5/-5) x 258(+5/-5)	10	175023
SFOH 6x2 GALV	2	120 x 180	393 x 358 x 60	293(+5/-5) x 258(+5/-5)	13.5	175025
SFOH 6x3 GALV	3	120 x 180	525.5 x 358 x 60	426(+5/-5) x 258(+5/-5)	16.6	124470
SFOH 6x4 GALV	4	120 x 180	658 x 358 x 60	558(+5/-5) x 258(+5/-5)	20.4	124471



Titel	Ramöppningar	Packningsutrymme	Yttermått WxHxD	Öppningens mått w x h	Vikt	Art. nr
SFOH 8x1 GALV	1	120 x 240	260.5 x 418 x 60	161(+5/-5) x 318(+5/-5)	10	175034
SFOH 2x3 AISI316	3	120 x 60	525.5 x 241 x 60	426(+5/-5) x 141(+5/-5)	13.4	245789
SFOH 8x2 GALV	2	120 x 240	393 x 418 x 60	293(+5/-5) x 318(+5/-5)	14.4	254323
SFOH 8x3 GALV	3	120 x 240	525.5 x 418 x 60	426(+5/-5) x 318(+5/-5)	18.4	254324
SFOH 8x4 GALV	4	120 x 240	658 x 418 x 60	558(+5/-5) x 318(+5/-5)	22.5	254325
SFOH 2x4 AISI316	4	120 x 60	658 x 241 x 60	558(+5/-5) x 141(+5/-5)	16.5	245790
SFOH 4x1 AISI316	1	120 x 120	260.5 x 299.5 x 60	161(+5/-5) x 200(+5/-5)	8	106163
SFOH 4x2 AISI316	2	120 x 120	393 x 299.5 x 60	293(+5/-5) x 200(+5/-5)	11.7	171353
SFOH 4x3 AISI316	3	120 x 120	525.5 x 299.5 x 60	426(+5/-5) x 200(+5/-5)	14.8	171354
SFOH 4x4 AISI316	4	120 x 120	658 x 299.5 x 60	558(+5/-5) x 200(+5/-5)	18.6	236043
SFOH 6x1 AISI316	1	120 x 180	260.5 x 358 x 60	161(+5/-5) x 258(+5/-5)	9	106164

Information om tätningsskomponenter


Tätningsskomponenter



stagbricka




tätningsskit



RM solid
kompensationsmodul



Wedge och Wedgekit



RM-modul med
Multidiameter™



hållarverktyg



förkomprimeringsverktyg



smörjmedel

Detaljerad information finns på [roxtec.com](https://www.roxtec.com).

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2026-01-13



Roxtec ® and Multidiameter ®
are registered trademarks of Roxtec
in Sweden and/or other countries.