



Roxtec knock-out frame doorvoer

Lichtgewicht doorvoer voor instorten

Het Roxtec knock-out frame (KOF) is een lichtgewicht doorvoer voor meerdere kabels, die wordt ingestort en die de locatie tijdens en na de bouw drooghoudt. De ingebouwde uitbreekdeksel zorgt voor afdichting totdat het deksel eruit wordt geslagen, voorafgaand aan de kabeldoorvoering en de installatie van de afdichtcomponenten. De standaard Roxtec RM afdichtmodulen zijn geschikt voor kabels van verschillende diameters en kunnen ook worden gebruikt om reservecapaciteit in de doorvoer te creëren.

De KOF met deksel kan ook reservecapaciteit bieden voor de toekomst. Met de KOF adapter kan de framediepte eenvoudig in stappen van 50 mm worden gewijzigd, zodat de KOF geschikt is voor wanden van uiteenlopende diktes en er geen instortblokken nodig zijn. De KOF heeft een geïntegreerde klikfunctie zodat de frames kunnen worden gekoppeld, om zo ruimtebesparende clusters te vormen.



- ☒ Corrosiebestendig
- ☒ Lichtgewicht
- ☒ Dicht tijdens de bouwfase

Producteigenschappen



Brandvertragend



IP/UL NEMA

Installatiestructuur



Beton

Montagetype



Instorten

Specificaties en certificaten

Brand

- ☒ E/EI-classificatie volgens EN 13501

Dichtheid

- ☒ IP 68

Afmetingen frame

mm/kg

De onderstaande frame-uitvoeringen zijn een beperkte selectie. Ga naar [roxtec.com](https://www.roxtec.com) voor het volledige assortiment frames en configuraties.

Titel	Frame-openingen	Vrije doorvoerruimte	Buitenafmetingen WxHxD	Afmetingen opening w x h	Gewicht	Art. nr.
KOF 6x1 D=100	1	120 x 180	226 x 324 x 100	187 x 285	0.6	249058



Gegevens van afdichtcomponenten


Afdichtcomponenten



fixeerplaat




afdichtset



Massieve RM
compensatiemodule



Wedge en Wedgekit



RM module met
Multidiameter™



pre-compressietools



vetstick

Accessoires

Ga naar [roxtec.com](https://www.roxtec.com) voor uitgebreide informatie.

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2025-12-18



Roxtec ® and Multidiameter ®
are registered trademarks of Roxtec
in Sweden and/or other countries.