



Roxtec H2 seal with SLA

Cable seal with adaption sleeve for attachment in drilled hole

The Roxtec H2 seal with SLA sleeve is a transit for one or two cables in round holes. The compression is integrated in the transit frame, so it seals by expansion. The entry seal has two halves with removable layers making it adaptable to cables of different sizes. The sleeve is threaded and is attached to the structure with a counter nut



- Area efficient
- Perfect for retrofit
- Quick and easy to install

Product characteristics



Fire rated Watertight

Structure of installation



Metal

Mounting type



Bolting

Ratings & certificates

Fire

- A-CLASS according to IMO 2010 FTP Code

Tightness

- Water: 2.5 bar (catastrophic)

Sealing components

Sealing components



Lubricant



SLA H2 kit

For detailed information, please visit roxtec.com.

Pre-configured transit kits

mm/kg



SLA H2 31 GALV



SLA H2 31 AISI316

Product	Configuration	Aperture dimensions \varnothing	Weight	Art. no
SLA H2 31 GALV		34 - 34	0.7	203782
SLA H2 31 AISI316		34 - 34	0.7	203774



The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2026-02-12



Roxtec ® and Multidiameter ®
are registered trademarks of Roxtec
in Sweden and/or other countries.