



Roxtec SPM™ HT-tetning

Tetning for metallrør til bruk når sveising ikke er tillatt, anbefalt eller ønsket.

Tetning for metallrør til bruk når sveising ikke er tillatt, anbefalt eller ønsket. Roxtec SPM™ HT (High Temperature) er en lettvekts, sveisefri gjennomføringsløsning for enkeltrør i metall som transporterer varme væsker med temperaturer opptil 150 °C. Tetningen er tilgjengelig i flere størrelser og kan tilpasses ulike rørdimensjoner, slik at den kan brukes på rør med diametere fra 8 til 56 mm og i ujevne åpninger. Rørtetningen monteres direkte inn i strukturer uten sveising og har indikatorer som viser når full kompresjon er oppnådd.



- Lettvekt
- Rask og enkel å installere
- Enkel å vedlikeholde og inspisere

Produktegenskaper



Brannklassifisert

Struktur for installasjon



Metall

Festetype



Eksisterende hull

Graderinger og sertifikater

Brann

- A-KLASSE i henhold til IMO 2010 FTP-kode

Tetningskomponentdata

Tetningskomponenter




SPM™ HT-tetning

For ytterligere informasjon, kan du besøke www.roxtec.com.



Forhåndskonfigurerte gjennomføringskit

mm/kg



Kapasitet (mengde x størrelse)	Utvendige mål ØxD (mm)	Vekt (kg)	Art.nr.
1x (8.0-12.0)	49 x 44	0.13	167582
1x (12.0-16.0)	51 x 44	0.14	165529
1x (16.0-20.0)	59 x 49	0.2	167584
1x (19.0-23.0)	64 x 49	0.21	165533
1x (24.0-28.0)	69 x 50	0.29	165535
1x (27.0-31.0)	72 x 50	0.3	165537
1x (32.0-36.0)	79 x 50	0.4	165539
1x (37.0-42.0)	88 x 50	0.42	165655
1x (41.4-45.4)	89 x 50	0.43	165527
1x (47.0-51.0)	95 x 50	0.4	165541
1x (52.0-56.0)	100 x 50	0.5	165543

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2026-09-19



Roxtec ® and Multidiameter ®
are registered trademarks of Roxtec
in Sweden and/or other countries.