



# **GK Firestop Sealing Kit**

GK 방화 씰링 키트는 선박 및 선박의 상부에 적용할 때 추천되고 있습니다. 팽창성 재료가 화재가 발생하거나 온도가 150°C 이상으로 상승했을 때 홀을 막기 위해 팽창하므로, 확실한 연기 차단 및 화재 예방 기능을 제공합니다. 이 키트는 다양한 원형 또는 타원형 슬리브에 설치할 수 있으며 , A-60 또는 A-0 적용을 위한 추가 절연이 필요하지 않습니다.



공간 효율성

빠르고 간편한 설치

제품 특장점



내화

설치 구조



장착 유형



볼트체결





기존 슬리

## 등급 및 인증

화재

IMO 2010 FTP 코드에 따른 A등급

## 씰링 컴포넌트 데이터

씰링 컴포넌트



GK FS SK

자세한 내용은 roxtec.com을 방문하십시오.

2024-04-05





### mm/kg





















GK FS SK 89 KIT

GK FS SK 140 KIT

GK FS SK 168 KIT

GK FS SK 219 KIT

GK FS SK 244 KIT

GK FS SK 273 KIT

GK FS SK 200x150 KIT

















GK FS SK 200x170 KIT GK FS SK 250x170 KIT GK FS SK 200x150 KIT NON-OPENABLE

GK FS SK 273 KIT NON-OPENABLE

GK FS SK 127 KIT NON-OPENABLE

GK FS SK 200x170 KIT NON-OPENABLE

GK FS SK 140 KIT NON-OPENABLE

GK FS SK 168 KIT NON-OPENABLE









GK FS SK 250x170 KIT NON-OPENABLE

GK FS SK 89 KIT NON-OPENABLE

GK FS SK 219 KIT NON-OPENABLE

GK FS SK 244 KIT NON-OPENABLE

구성	구성	<b>홀 치수</b> Ø	무게	Art. 번호
GK FS SK 89 KIT		84 - 89	0.7	197464
GK FS SK 127 KIT		107 - 127	1	197465
GK FS SK 140 KIT		120 - 140	0.8	197466
GK FS SK 168 KIT		138 - 168	1.2	197467
GK FS SK 219 KIT		179 - 219	1.6	197468
GK FS SK 244 KIT		204 - 244	1.8	197469
GK FS SK 273 KIT		233 - 273	1.9	197470
GK FS SK 200x150 KIT		169 - 182	1.3	197472
GK FS SK 200x170 KIT		176 - 189	1.4	197474
GK FS SK 250x170 KIT		208 - 224	1.6	197475
GK FS SK 200x150 KIT NON-OPENABLE		169 - 182	1.2	197813
GK FS SK 273 KIT NON-OPENABLE		233 - 273	2.3	197814
GK FS SK 127 KIT NON-OPENABLE		107 - 127	0.7	197817
GK FS SK 200x170 KIT NON-OPENABLE		176 - 189	1.3	197818
GK FS SK 140 KIT NON-OPENABLE		120 - 140	0.7	197820
GK FS SK 168 KIT NON-OPENABLE		138 - 168	1.1	197821
GK FS SK 250x170 KIT NON-OPENABLE		208 - 224	1.5	197822
GK FS SK 89 KIT NON-OPENABLE		84 - 89	0.6	197823
GK FS SK 219 KIT NON-OPENABLE		179 - 219	1.4	197824
GK FS SK 244 KIT NON-OPENABLE		204 - 244	1.6	197825

2/3 2024-04-05



### roxtec.com에서 솔루션에 대해 더 자세히 알아보세요

https://www.roxtec.com/linktransit/ko-kr/solution/8843



The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2024-04-05

3/3 2024-04-05